SUMMARY OF EUROPEAN HIGH-SPEED RAIL

NOISE AND VIBRATION MEASUREMENTS

HMMH Report No. 293630-2

April 1996

Prepared by:

Harris Miller Miller & Hanson Inc. 15 New England Executive Park Burlington, Massachusetts 01803

Submitted to:

hmmh

DeLeuw, Cather & Company 1133 15th Street NW Washington, DC 20005-2701

HARRIS MILLER MILLER & HANSON INC.

Consultants in Noise and Vibration Control

.

TABLE OF CONTENTS

LIST	OF FIGU	RES	iii
LIST	OF TAB	LES	iv
1.	MEAS 1.1 1.2 1.3	UREMENT LOCATIONS	1 2 4 5
2.	MEAS 2.1 2.2 2.3	UREMENT PROCEDURES AND EQUIPMENT	55 55 60 65
3.	NOISE 3.1 3.2 3.3	MEASUREMENT RESULTS	67 67 67 68
4.	GROU 4.1 4.2 4.3	ND-BORNE VIBRATION MEASUREMENT RESULTS	71 71 71 72
5.	GROU 5.1 5.2	ND-BORNE VIBRATION PROPAGATION TEST RESULTS Test Analysis Procedures Summary of Test Results	74 74 74
APP	ENDIX A	: A-WEIGHTED TRAIN NOISE MEASUREMENT DATA	A-1
APP	ENDIX B	: TRAIN NOISE SPECTRA	B-1
APP	ENDIX C	: GROUND-BORNE VIBRATION LEVELS FOR TRAIN EVENTS	C-1
APP	ENDIX D	GROUND-BORNE VIBRATION SPECTRA FOR TRAIN EVENTS	D-1

LIST OF FIGURES

FIGURE 1. FRENCH MEASUREMENT SITE VICINITY MAP	3
FIGURE 2. LOCATION MAP OF FRENCH MEASUREMENT SITES D, G AND H 9)
FIGURE 3. PHOTOGRAPH OF FRENCH MEASUREMENT SITE D 10)
FIGURE 4A. PLAN VIEW OF FRENCH MEASUREMENT SITE D 11	l
FIGURE 4B. CROSS-SECTIONAL VIEW OF FRENCH MEASUREMENT SITE D 12	2
FIGURE 5. PHOTOGRAPH OF FRENCH MEASUREMENT SITE G 13	3
FIGURE 6A. PLAN VIEW OF FRENCH MEASUREMENT SITE G 14	4
FIGURE 6B. CROSS-SECTIONAL VIEW OF FRENCH MEASUREMENT SITE G 15	5
FIGURE 7. PHOTOGRAPH OF FRENCH MEASUREMENT SITE H 16	6
FIGURE 8A. PLAN VIEW OF FRENCH MEASUREMENT SITE H 17	7
FIGURE 8B. CROSS-SECTIONAL VIEW OF FRENCH MEASUREMENT SITE H 18	8
FIGURE 9. PHOTOGRAPH OF FRENCH MEASUREMENT SITE K 19	9
FIGURE 10A. PLAN VIEW OF FRENCH MEASUREMENT SITE K 20	0
FIGURE 10B. CROSS-SECTIONAL VIEW OF FRENCH MEASUREMENT SITE K 2	1
FIGURE 11. PHOTOGRAPH OF TGV HAUTE PICARDIE STATION 22	2
FIGURE 12. ITALIAN MEASUREMENT SITE VICINITY MAP 23	3
FIGURE 13. PHOTOGRAPH OF ITALIAN MEASUREMENT SITE 2 24	4
FIGURE 14A. PLAN VIEW OF ITALIAN MEASUREMENT SITE 2 25	5
FIGURE 14B. CROSS-SECTIONAL VIEW OF ITALIAN MEASUREMENT SITE 2 24	6
FIGURE 15. PHOTOGRAPH OF ITALIAN MEASUREMENT SITE 3 2'	7
FIGURE 16A. PLAN VIEW OF ITALIAN MEASUREMENT SITE 3 23	8
FIGURE 16B. CROSS-SECTIONAL VIEW OF ITALIAN MEASUREMENT SITE 3 2'	9
FIGURE 17. PHOTOGRAPH OF ITALIAN MEASUREMENT SITE 4	0
FIGURE 18A. PLAN VIEW OF ITALIAN MEASUREMENT SITE 4	1
FIGURE 18B. CROSS-SECTIONAL VIEW OF ITALIAN MEASUREMENT SITE 4 3	2
FIGURE 19. PHOTOGRAPH OF PARMA STATION	3
FIGURE 20. LOCATION MAP FOR SWEDISH MEASUREMENT SITES 1, 2 AND 3 3	4
FIGURE 21. LOCATION MAP FOR SWEDISH MEASUREMENT SITE 4	5
FIGURE 22. LOCATION MAP FOR SWEDISH MEASUREMENT SITE 5	6
FIGURE 23. PHOTOGRAPH OF SWEDISH MEASUREMENT SITE 1	7
FIGURE 24A. PLAN VIEW OF SWEDISH MEASUREMENT SITE 1	8
FIGURE 24B. CROSS-SECTIONAL VIEW OF SWEDISH MEASUREMENT SITE 1 3	9
FIGURE 25. PHOTOGRAPH OF SWEDISH MEASUREMENT SITE 2 4	-0
FIGURE 26A. PLAN VIEW OF SWEDISH MEASUREMENT SITE 2 4	1
FIGURE 26B. CROSS-SECTIONAL VIEW OF SWEDISH MEASUREMENT SITE 2 4	+2
FIGURE 27. PHOTOGRAPH OF SWEDISH MEASUREMENT SITE 3A 4	13
FIGURE 28A. PLAN VIEW OF SWEDISH MEASUREMENT SITE 3A	4
FIGURE 28B. CROSS-SECTIONAL VIEW OF SWEDISH MEASUREMENT SITE 3A 4	15
FIGURE 29. PHOTOGRAPH OF SWEDISH MEASUREMENT SITE 3B 4	16
FIGURE 30A. PLAN VIEW OF SWEDISH MEASUREMENT SITE 3B	17
FIGURE 30B. CROSS-SECTIONAL VIEW OF SWEDISH MEASUREMENT SITE 3B 4	18
FIGURE 31. PHOTOGRAPH OF SWEDISH MEASUREMENT SITE 4 4	19

LIST OF FIGURES (CONTINUED)

FIGURE 32A. PLAN VIEW OF SWEDISH MEASUREMENT SITE 4	50
FIGURE 32B. CROSS-SECTIONAL VIEW OF SWEDISH MEASUREMENT SITE 4	51
FIGURE 33. PHOTOGRAPH OF SWEDISH MEASUREMENT SITE 5	52
FIGURE 34A. PLAN VIEW OF SWEDISH MEASUREMENT SITE 5	53
FIGURE 34B. CROSS-SECTIONAL VIEW OF SWEDISH MEASUREMENT SITE 5	54
FIGURE 35. GROUND-BORNE VIBRATION PROPAGATION TEST PROCEDURE	66
FIGURE 36. HIGH-SPEED TRAIN MAXIMUM NOISE LEVEL VS. SPEED	69
FIGURE 37. HIGH-SPEED TRAIN SOUND EXPOSURE LEVEL VS. SPEED	70
FIGURE 38. HIGH-SPEED TRAIN VIBRATION LEVELS VS. DISTANCE	73
FIGURE 39. LINE-SOURCE TRANSFER MOBILITY AT THE TEST SITES	76
FIGURE 40. NORMALIZED TRAINSET FORCE DENSITY FUNCTIONS	77
FIGURE 41. PROJECTED VIBRATION - SITE D (FRANCE) TRANSFER MOBILITY	78
FIGURE 42. PROJECTED VIBRATION - SITE 3B (SWEDEN) TRANSFER MOBILITY	79
FIGURE 43. PROJECTED VIBRATION VELOCITY USING X2000 FORCE DENSITY	80

LIST OF TABLES

TABLE 1.	FIELD INSTRUMENTS USED FOR TRAIN NOISE MEASUREMENTS	56
TABLE 2.	INSTRUMENTS USED FOR TRAIN NOISE MEASUREMENTS IN FRANCE	57
TABLE 3.	INSTRUMENTS USED FOR TRAIN NOISE MEASUREMENTS IN ITALY	58
TABLE 4.	INSTRUMENTS USED FOR TRAIN NOISE MEASUREMENTS IN SWEDEN	59
TABLE 5.	FIELD INSTRUMENTS USED FOR GROUND VIBRATION MEASUREMENTS	61
TABLE 6.	INSTRUMENTS USED FOR VIBRATION MEASUREMENTS IN FRANCE	62
TABLE 7.	INSTRUMENTS USED FOR VIBRATION MEASUREMENTS IN ITALY	63
TABLE 8.	INSTRUMENTS USED FOR VIBRATION MEASUREMENTS IN SWEDEN	64

 \mathcal{X}_{i}^{i}

SUMMARY OF EUROPEAN HIGH-SPEED RAIL NOISE AND VIBRATION MEASUREMENTS

Noise and ground-borne vibration measurements of European high-speed train operations were carried out during May 1995. The measurements were performed by the staff of Harris Miller Miller & Hanson Inc. (HMMH) for the U.S. Federal Railroad Administration (FRA), under subcontract to De Leuw Cather & Company (DCCO). The purpose of this program was to document wayside noise and vibration levels for representative European high-speed trainsets as a function of distance, speed and consist, with the ultimate objective of developing suitable guidance manual models for high-speed rail noise and vibration projection.

Wayside noise and vibration measurements were carried out on high-speed trains in three countries, including the TGV and Eurostar trains in France, the Pendolino trains in Italy and the X2000 trains in Sweden. The measurement locations, procedures, equipment and results are described below.

1. MEASUREMENT LOCATIONS

High-speed train noise and vibration measurement locations were selected by HMMH based on candidate sites identified by local acoustical consulting organizations acting as project liaisons in each country. These liaisons included Commins Acoustical Workshop in France, Phoneco in Italy and Ingemansson in Sweden. The candidate measurement sites were identified based on guidance provided by HMMH with regard to geographical characteristics, train operations and track configuration.

The guidance provided with regard to site geographical characteristics was based primarily on measurement logistics as follows:

- The sites in each country should be located in the same general region, within a one-hour (or less) drive of each other.
- The sites should be in generally open, level areas that are accessible by van.
- The sites should allow access for the placement of instrumentation within an area extending between 12.5 and 75 meters from the near track centerline, along a 60-meter segment of the railroad line, with no intervening obstacles or major roads.
- The sites should not be very close to sources of significant noise or vibration that could contaminate the measurements, such as major roads, airports, industrial plants, construction sites or agricultural equipment.

Based on the measurement objectives, the desired conditions with regard to train operations and track configuration were as follows:

- One primary site in each country where trains operate at or above grade along a straight section of track at or near the maximum speed for the rail system.
- Additional at-grade or above-grade sites where trains operate at intermediate and low speeds, to investigate the speed dependence of train noise and vibration.

- Sites where trains operate on a high embankment or elevated structure.
- Sites where trains operate in a low cut or behind barriers where the noise sources on the train are shielded from view.
- For tilt-trains (i.e. the X2000 and Pendolino), sites on curves where the tilt mechanisms are fully employed.

The candidate sites were visited by HMMH and liaison consultant representatives during the period from 24 April through 3 May 1995. Based on these visits, the final measurement sites were selected by HMMH. The sites and specific measurement locations in each country are described below. It should be noted that because the sites were selected from a pool of candidate sites, the site designations in each country are not necessarily in consecutive alphabetical or numerical order.

1.1 French Measurement Sites

Measurements were carried out on 9-11 May 1995 at four sites along the French National Railway's TGV Nord line to the north of Paris. The general locations of these sites, designated as sites D, G, H and K, are indicated in Figures 1 and 2. Additional measurements along this line were performed on 12 May 1995 at the TGV Haute Picardie Station. The maximum train speed along this line is 300 kph (186 mph).

Train operations along the TGV Nord line include both single and double TGV consists, as well as Eurostar trains. The standard TGV consist includes 2 power cars, 2 transition cars and eight coaches with a total length of 237.5 meters; the double consists are 475 meters long. In all cases, the pantograph was observed to be raised on the trailing power car of each standard TGV consist. The Eurostar train consist includes 2 power cars and 18 coaches, with a total length of 393.7 meters. For the Eurostar trains, the pantograph was observed to be raised on both the leading and trailing power cars.

The French noise and vibration test sites and measurement locations are described below.

Site D. Site D (see Figure 3), located on the southbound (east) side of the TGV Nord line to the east of the village of Baron, was selected as the primary site in France. At this site, two tracks are located on an embankment approximately 3 meters high, with a track separation of 4.5 meters. The tracks consist of continuous welded rail on 0.5-m spaced concrete ties and ballast. Twenty-five trains were monitored at this site between 12:00 and 18:45 on 10 May 1995, with speeds of 269-296 kph (167-184 mph).

Noise and ground-borne vibration measurements were made along a dirt road running perpendicular to the rail line through a level, cultivated field. In addition to the train measurements, ground vibration propagation tests were also performed by generating ground impacts at points along a line parallel to the tracks near the right-of-way fence. Figures 4A and 4B provide plan and cross-sectional drawings that illustrate the measurement and impact locations. As shown in these figures, train noise measurements were made at distances of 25, 50 and 75 meters from the near (southbound) track center line, at a height of 1.5 meters above ground with an additional 4-meter high position at the 25 meter reference location. Similarly, ground vibration measurements were made at distances of 17.5, 25, 37.5, 50, 62.5 and 75 meters from the near track center line. Vibration propagation tests were made by generating impacts on the ground at points spaced 6 meters apart along a line 60 meters long, centered at the measurement line, at a distance of 17 meters from the near track center line.

European High-Speed Rail Noise and Vibration Measurements	Page 3
HMMH Report No. 293630-2	April 1996

Site G. Site G (see Figure 5) was located on the southbound (east) side of the TGV Nord line to the east of Beaulieu le Neuf. At this site, the two tracks are located in a cut approximately 15 meters deep, with a track separation of 4.5 meters. The tracks consist of continuous welded rail on 0.5-m spaced concrete ties and ballast. Twenty trains were monitored at this site between 16:30 and 19:05 on 9 May 1995, with speeds of 154-294 kph (96-183 mph).

Only noise measurements were made at Site G. These were made along tractor paths in a cultivated field, about 150 meters north of a roadway bridge crossing over the tracks. Figures 6A and 6B provide plan and cross-sectional drawings that illustrate the measurement locations. As shown in these figures, train noise measurements were made at distances of 44 and 75 meters from the near (southbound) track center line, at a height of 1.5 meters above ground with an additional 4-meter high position at the 44 meter location. The view of the trains was unshielded at the 44m/4m-high position, partially shielded at the 44m/1.5m-high position and totally shielded at the 75m/1.5m-high position.

Site H. Site H (see Figure 7) was located on the northbound (west) side of the TGV Nord line to the east of the village of Ducy. At this site, the two tracks are located on an embankment approximately 5-meters high, shielded by a concrete barrier wall about 370-m long and 3-m high, mounted on the embankment approximately 5 meters from the near (northbound) track center line. The tracks consist of continuous welded rail on 0.5-m spaced concrete ties and ballast, with a track separation of 4.5 meters. Fifteen trains were monitored at this site between 11:05 and 13:20 on 11 May 1995, with speeds of 267-298 kph (166-185 mph).

Only noise measurements were made at Site H. These were made in an open, uncultivated field along two lines running perpendicular to the rail line. One of these lines was located at the mid-point of the barrier while the other was located about 110 meters north of the north end of the barrier wall. Figures 8A and 8B provide plan and cross-sectional drawings that illustrate the measurement locations. As shown in these figures, train noise measurements behind the barrier were made at distances of 25, 50 and 75 meters from the near (northbound) track center line, at a height of 1.5 meters above ground with an additional 4-meter high position at the 25 meter reference location. At the unshielded location north of the barrier, measurements were made at distances of 25 and 50 meters from the near (northbound) track center line, at a height of 1.5 meters above track centerline, at a height of 1.5 meters from the near (northbound) track center line.

Site K. Site K (see Figure 9) was located on the northbound (west) side of the TGV Nord line to the west of Charles De Gaulle Airport. At this site, the two tracks are located on an embankment approximately 2-meters high, with a track separation of 4.5 meters. The tracks consist of continuous welded rail on 0.5-m spaced concrete ties and ballast. Fifteen trains were monitored at this site between 16:30 and 19:00 on 11 May 1995, with speeds of 145-216 kph (90-134 mph).

Noise and ground-borne vibration measurements were made in a lightly-cultivated field adjacent to the tracks. Figures 10A and 10B provide plan and cross-sectional drawings that illustrate the measurement locations. As shown in these figures, train noise measurements were made at distances of 25 and 50 meters from the near (northbound) track center line, at a height of 1.5 meters above ground with an additional 4-meter high position at the 25 meter reference location. Similarly, ground vibration measurements were made at distances of 25 and 50 meters from the near track center line.

TGV Haute Picardie Station. This site (see Figure 11) was at a new train station on the TGV Nord line between Paris and Lille. Four tracks pass through the station, with through trains using the two center

European High-Speed Rail Noise and Vibration Measurements	Page 4
HMMH Report No. 293630-2	April 1996

tracks. Through train noise measurements were performed on the northbound station platform between 18:00 and 18:30 on 12 May 1995 to determine patron noise exposure. Six trains, operating at or near the maximum speed of 300 kph (186 mph) were monitored at distances of about 15 meters from the northbound main line track and 20 meters from the southbound main line track.

1.2 Italian Measurement Sites

Measurements were carried out on 15-18 May 1995 at three sites along the Milano-Bologna segment of the Italian National Railway's main line between the cities of Parma and Reggio Emilia. The general locations of these sites, designated as sites 2, 3 and 4, are indicated in Figure 12. Additional measurements were performed on 18 May 1995 at the Parma Station.

Train operations along the Milano-Bologna main line include a variety of passenger and freight trains. Of primary interest were the Pendolino ETR-450 high-speed tilt trains, which operate at a maximum speed of about 200 kph (125 mph). The standard Pendolino consist includes two end units and seven other cars, with a total length of 236.6 meters. The pantograph was observed to be raised on the sixth car only.

The Italian noise and vibration test sites and measurement locations are described below.

Site 2. Site 2 (see Figure 13) was located on the northbound side of the railroad line near the town of Cade. At this site, three tracks are located at grade, including a two main line tracks located 3.7 meters apart, plus a siding located 5.5 meters from the northbound main line track between the measurement site and the main line. The main line tracks consist primarily of continuous welded rail on 0.6-m spaced concrete ties and ballast, although several rail joints were observed in the southbound track in this vicinity. Three Pendolino trains were monitored at this site between 20:00 and 21:00 on 15 May 1995, with speeds of 190-194 kph (118-121 mph).

Noise and ground-borne vibration measurements at Site 2 were made along a tractor path running perpendicular to the rail line through a level, cultivated field. Figures 14A and 14B provide plan and cross-sectional drawings that illustrate the measurement locations. As shown in these figures, train noise measurements were made at distances of 25, 50 and 75 meters from the near (northbound) track center line, at a height of 1.5 meters above ground with an additional 4-meter high position at the 25 meter reference location. Similarly, ground vibration measurements were made at distances of 12.5, 25, 50 and 75 meters from the near track center line.

Site 3 (see Figure 15) was located in an asphalt-paved parking lot on the northbound side of the railroad line, on the inside of a curved section of track in the city of Reggio Emilia. The curve radius at this location was estimated to be 880 meters (about 2,900 feet). At this site, two tracks are located on an embankment approximately 1.5 meters above grade, separated from the measurement site by a grassy ditch. The tracks consist of continuous welded rail on 0.6-m spaced concrete ties and ballast, and welded joints were visible in both tracks near the measurement positions. Four Pendolino trains were monitored at this site between about 20:00 and 21:00 on 17 May 1995, with speeds of 130-154 kph (81-96 mph).

Noise and ground-borne vibration measurements were made at several locations in the parking lot. Figures 16A and 16B provide plan and cross-sectional drawings that illustrate the measurement locations. As shown in these figures, train noise measurements were made at distances of 25, 50 and 75 meters from the near (northbound) track center line, at a height of 1.5 meters above ground with an additional 5-meter

high position at the 25 meter reference location. Ground vibration measurements were made at distances of 17.5, 25, 50 and 75 meters from the near (northbound) track center line.

Site 4. Site 4 (see Figure 17), located on the southbound side of the railroad line near the town of Cella, was selected as the primary site in Italy. At this site, two tracks are located on an embankment approximately 1.5 meters high, with a track separation of 3.7 meters. The tracks consist of continuous welded rail on 0.6-m spaced concrete ties and ballast. Eight Pendolino trains were monitored at this site during two periods, between about 9:00 and 17:00 on 16 May 1995 and between about 8:00 and 10:00 on 18 May 1995. Train speeds during the measurements were in the range of 175-196 kph (109-122 mph).

Noise and ground-borne vibration measurements at Site 4 were made in a mowed, grassy field adjacent to the railroad line. In addition to the train measurements, ground vibration propagation tests were also performed by generating ground impacts at points along a line parallel to the tracks on the embankment. Figures 18A and 18B provide plan and cross-sectional drawings that illustrate the measurement and impact locations. As shown in these figures, train noise measurements were made at distances of 25, 50 and 75 meters from the near (southbound) track center line, at a height of 1.5 meters above ground with an additional 5-meter high position at the 25 meter reference location. Similarly, ground vibration measurements were made at distances of 10, 25, 37.5, 50, 62.5 and 75 meters from the near track center line. Vibration propagation tests were made by generating impacts on the ground at points spaced 6 meters apart along a line 60 meters long, centered at the measurement line, at a distance of 3 meters from the near track center line.

Parma Station. This site (see Figure 19) was on the center northbound platform at Parma Station. While most trains stop at the station, some through trains, including most Pendolinos, pass by the station platforms at high speed. Train noise measurements were performed on the center northbound station platform between about 20:00 and 21:00 on 18 May 1995 to determine patron noise exposure. Eleven trains, including four Pendolinos, were monitored at distances of about 4 meters from the northbound track and 8 meters from the southbound track.

1.3 Swedish Measurement Sites

Measurements were carried out on 22-24 May 1995 at six sites along the Stockholm-Goteborg main line of the Swedish State Railway between the cities of Alingsas and Herrljunga. The general locations of these sites, designated as sites 1, 2, 3A, 3B, 4 and 5, are indicated in Figures 20, 21 and 22.

Train operations along the Stockholm-Goteborg main line include a variety of passenger and freight trains. Of primary interest were the X2000 high-speed tilt trains, which operate at a maximum speed of about 200 kph (125 mph). The standard X2000 consist is 140 meters long and includes one power car with raised pantograph, located at the west end of the train, one cab unit, located at the east end of the train, and four coaches.

The Swedish noise and vibration test sites and measurement locations are described below.

Site 1. Site 1 (see Figure 23) was located on the eastbound (north) side of the railroad line in Savelund near Alingsas. At this site, two tracks are located on a tall embankment approximately 4-5 meters above grade, with a track separation of 4.5 meters. The tracks consist of continuous welded rail weighing 50

European High-Speed Rail Noise and Vibration Measurements	Page 6
HMMH Report No. 293630-2	April 1996

kg/m, attached to 0.7-m spaced concrete ties with "Hambo" type rail fasteners and supported on stone ballast. Eleven X2000 trains were monitored at this site between 9:20 and 18:50 on 22 May 1995, with speeds of 153-177 kph (95-110 mph). There is a slight curve in the tracks at this location, and westbound trains sometimes emitted brake squeal while passing this site.

Noise measurements only were made at Site 1, in an uncultivated field. Figures 24A and 24B provide plan and cross-sectional drawings that illustrate the measurement locations. As shown in these figures, the measurements were made at distances of 25 and 50 meters from the near (eastbound) track centerline, at a height of 1.5 meters above the ground. At these positions, the edge of the embankment provided some shielding of the westbound track rails.

Site 2. Site 2 (see Figure 25) was located on the eastbound (north) side of the railroad line in Savelund near Alingsas, just east of Site 1. While the track construction is the same as at Site 1, the tracks at Site 2 are located in a cut approximately 4 meters deep. The measurements at Site 2 coincided with the measurements at Site 1 for the same eleven trains.

Noise measurements only were made at Site 2, in an uncultivated field. Figures 26A and 26B provide plan and cross-sectional drawings that illustrate the measurement locations. As shown in these figures, the measurements were made at distances of 20, 40 and 65 meters from the near (eastbound) track centerline at a height of 1.5 meters above the ground, with an additional 5 meter high position at the 40 meter measurement location. At these positions, the edge of the cut configuration provided varying degrees of train noise shielding.

Site 3A. Site 3A (see Figure 27), located on the eastbound (north) side of the railroad line near the village of Torp, was selected as the primary noise measurement site in Sweden. At this site, two tracks are located on a low embankment, about 1 meter high, with a track separation of 4.5 meters. The tracks consist of continuous welded rail weighing 50 kg/m, attached to 0.7-m spaced concrete ties with "Hambo" type rail fasteners and supported on stone ballast. Eleven X2000 trains were monitored at this site between 9:20 and 18:30 on 23 May 1995, with speeds of 159-188 kph (99-117 mph).

The noise measurements at Site 3A were made in a cultivated field. Figures 28A and 28B provide plan and cross-sectional drawings that illustrate the measurement locations. As shown in these figures, the measurements were made at distances of 25, 50 and 75 meters from the near (eastbound) track center line, at a height of 1.5 meters above ground with an additional 5-meter high position at the 25 meter reference location.

Site 3B. Site 3B (see Figure 29), located on the westbound (south) side of the railroad line near the village of Torp and just east of Site 3A, was selected as the primary ground-borne vibration measurement site in Sweden. At this site, the two tracks are located at grade, with a construction similar to Site 3A except that the track separation was 9.3 meters at Site 3B. The measurements at Site 3B coincided with the measurements at Site 3A for the same eleven trains.

Both train vibration measurements and ground vibration propagation tests were performed at Site 3B. For the propagation tests, ground impacts were generated at points along a line parallel to the tracks. Figures 30A and 30B provide plan and cross-sectional drawings that illustrate the vibration measurement and impact locations. As shown in these figures, ground vibration measurements were made at distances of 7.5, 15, 25, 37.5, 50 and 62.5 meters from the near track center line. Vibration propagation tests were

made by generating impacts on the ground at points spaced 6 meters apart along a line 60 meters long, centered at the measurement line, at a distance of 4 meters from the near track center line.

Site 4. Site 4 (see Figure 31) was located on the eastbound (north) side of the railroad line in the village of Ugglegardet. At this site, the two tracks are curved and on a 2-meter high embankment, with a track separation of 4.5 meters. The tracks consist of continuous welded rail weighing 50 kg/m, attached to 0.7-m spaced concrete ties with "Hambo" type rail fasteners and supported on stone ballast. Five X2000 trains were monitored at this site between 9:20 and 13:50 on 24 May 1995, with speeds of 72-183 kph (45-114 mph).

Both noise and ground-borne vibration measurements were made at Site 4. The noise measurements were made in a cultivated field beyond the road that runs along the tracks while the ground vibration measurements were made in an uncultivated area between the road and the tracks. Figures 32A and 32B provide plan and cross-sectional drawings that illustrate the measurement locations. As shown in these figures, train noise measurements were made at distances of 25, 50 and 75 meters from the near (eastbound) track center line, at a height of 1.5 meters above ground with an additional 5-meter high position at the 25 meter reference location. The ground vibration measurements were made at distances of 7.5 and 15 meters from the near track center line.

Site 5. Site 5 (see Figure 33) was located on the eastbound (north) side of the railroad line near the village of Holmen, to the west of Herrljunga. At this site, the two tracks are located on a low embankment about 1.5 meters high, with a track separation of 4.5 meters. The tracks consist of continuous welded rail weighing 50 kg/m, on 0.7-m spaced concrete ties and stone ballast. The rails are attached to the ties using "Fist" type rail fasteners on the eastbound track and "Hambo" type rail fasteners on the westbound track. Six X2000 trains were monitored at this site between 16:30 and 19:40 on 24 May 1995, with speeds of 114-187 kph (71-116 mph).

Both noise and ground-borne vibration measurements were made at Site 5, along a dirt road running perpendicular to the tracks. Figures 34A and 34B provide plan and cross-sectional drawings that illustrate the measurement locations. As shown in these figures, train noise measurements were made at distances of 25, 50 and 75 meters from the near (eastbound) track center line, at a height of 1.5 meters above ground with an additional 5-meter high position at the 25 meter reference location. The ground vibration measurements were made at distances of 7.5, 15, 25 and 50 meters from the near track center line.

European High-Speed Rail Noise and Vibration Measurements HMMH Report No. 293630-2



FIGURE 1. FRENCH MEASUREMENT SITE VICINITY MAP

European High-Speed Rail Noise and Vibration Measurements HMMH Report No. 293630-2



FIGURE 2. LOCATION MAP OF FRENCH MEASUREMENT SITES D, G AND H



FIGURE 3. PHOTOGRAPH OF FRENCH MEASUREMENT SITE D



FIGURE 4A. PLAN VIEW OF FRENCH MEASUREMENT SITE D



FIGURE 4B. CROSS-SECTIONAL VIEW OF FRENCH MEASUREMENT SITE D





European High-Speed Rail Noise and Vibration Measurements HMMH Report No. 293630-2

Page 14 April 1996



FIGURE 6A. PLAN VIEW OF FRENCH MEASUREMENT SITE G

Page 15 April 1996



FIGURE 6B. CROSS-SECTIONAL VIEW OF FRENCH MEASUREMENT SITE G



FIGURE 7. PHOTOGRAPH OF FRENCH MEASUREMENT SITE H

Page 17 April 1996



FIGURE 8A. PLAN VIEW OF FRENCH MEASUREMENT SITE H

Page 18 April 1996



FIGURE 8B. CROSS-SECTIONAL VIEW OF FRENCH MEASUREMENT SITE H



FIGURE 9. PHOTOGRAPH OF FRENCH MEASUREMENT SITE K



FIGURE 10A. PLAN VIEW OF FRENCH MEASUREMENT SITE K

Page 21 April 1996



FIGURE 10B. CROSS-SECTIONAL VIEW OF FRENCH MEASUREMENT SITE K



FIGURE 11. PHOTOGRAPH OF TGV HAUTE PICARDIE STATION

European High-Speed Rail Noise and Vibration Measurements HMMH Report No. 293630-2

Page 23 April 1996



FIGURE 12. ITALIAN MEASUREMENT SITE VICINITY MAP



FIGURE 13. PHOTOGRAPH OF ITALIAN MEASUREMENT SITE 2

Page 25 April 1996



FIGURE 14A. PLAN VIEW OF ITALIAN MEASUREMENT SITE 2

Page 26 April 1996



FIGURE 14B. CROSS-SECTIONAL VIEW OF ITALIAN MEASUREMENT SITE 2



FIGURE 15. PHOTOGRAPH OF ITALIAN MEASUREMENT SITE 3



FIGURE 16A. PLAN VIEW OF ITALIAN MEASUREMENT SITE 3







FIGURE 17. PHOTOGRAPH OF ITALIAN MEASUREMENT SITE 4



FIGURE 18A. PLAN VIEW OF ITALIAN MEASUREMENT SITE 4

.



FIGURE 18B. CROSS-SECTIONAL VIEW OF ITALIAN MEASUREMENT SITE 4


FIGURE 19. PHOTOGRAPH OF PARMA STATION

European High-Speed Rail Noise and Vibration Measurements HMMH Report No. 293630-2



FIGURE 20. LOCATION MAP FOR SWEDISH MEASUREMENT SITES 1, 2 AND 3



FIGURE 21. LOCATION MAP FOR SWEDISH MEASUREMENT SITE 4

European High-Speed Rail Noise and Vibration Measurements HMMH Report No. 293630-2



FIGURE 22. LOCATION MAP FOR SWEDISH MEASUREMENT SITE 5



FIGURE 23. PHOTOGRAPH OF SWEDISH MEASUREMENT SITE 1



FIGURE 24A. PLAN VIEW OF SWEDISH MEASUREMENT SITE 1

ł







FIGURE 25. PHOTOGRAPH OF SWEDISH MEASUREMENT SITE 2



FIGURE 26A. PLAN VIEW OF SWEDISH MEASUREMENT SITE 2



FIGURE 26B. CROSS-SECTIONAL VIEW OF SWEDISH MEASUREMENT SITE 2



FIGURE 27. PHOTOGRAPH OF SWEDISH MEASUREMENT SITE 3A



FIGURE 28A. PLAN VIEW OF SWEDISH MEASUREMENT SITE 3A

Page 45 April 1996



FIGURE 28B. CROSS-SECTIONAL VIEW OF SWEDISH MEASUREMENT SITE 3A



FIGURE 29. PHOTOGRAPH OF SWEDISH MEASUREMENT SITE 3B



FIGURE 30A. PLAN VIEW OF SWEDISH MEASUREMENT SITE 3B

Page 48 April 1996



FIGURE 30B. CROSS-SECTIONAL VIEW OF SWEDISH MEASUREMENT SITE 3B



FIGURE 31. PHOTOGRAPH OF SWEDISH MEASUREMENT SITE 4



FIGURE 32A. PLAN VIEW OF SWEDISH MEASUREMENT SITE 4



Page 51 April 1996



FIGURE 32B. CROSS-SECTIONAL VIEW OF SWEDISH MEASUREMENT SITE 4



FIGURE 33. PHOTOGRAPH OF SWEDISH MEASUREMENT SITE 5



FIGURE 34A. PLAN VIEW OF SWEDISH MEASUREMENT SITE 5

Page 54 April 1996



FIGURE 34B. CROSS-SECTIONAL VIEW OF SWEDISH MEASUREMENT SITE 5

2. MEASUREMENT PROCEDURES AND EQUIPMENT

2.1 Noise Measurements

All noise measurements were made using one-half inch pre-polarized condenser microphones with preamplifiers and/or amplifiers, protected by a windscreen. All microphones were supported by a tripod with a mast extending to the required height, except for the in-station measurements where hand-held sound level meters were used.

The amplified noise signals from the measurement microphones were recorded on magnetic tape, using multi-channel digital audio tape (DAT) recorders for subsequent laboratory analysis. Calibrations, traceable to the U.S. National Institute of Standards and Technology (NIST), were carried out before and after each set of measurements using an acoustical calibrator.

Train speeds were measured using a radar speed detector, and each train event was also documented on videotape to provide a record of specific train consist details. Additional documentation was provided on field data sheets and by voice annotations on the audio and video recordings.

A list of the field instrumentation, including manufacturers, models and serial numbers, is provided in Table 1. Tables 2, 3 and 4 indicate the specific instrumentation used in France, Italy and Sweden, respectively, at each measurement site and position, referenced to the equipment codes in Table 1.

TABLE 1. FIELD INSTRUMENTS USED FOR TRAIN NOISE MEASUREMENTS

EQUIPMENT TYPE	EQUIPMENT CODE	MANUFACTURER	MODEL	SERIAL NUMBER
	M1	Bruel & Kjaer	4155	1095134
	M2	Brucl & Kjaer	4155	1786100
	M3	Bruel & Kjaer	4155	1817577
Microphone	M4	Bruel & Kjaer	JFACTURERMODELNnel & Kjaer41551nel & Kjaer41551GenRad1972-96001GenRad1972-96001GenRad1972-96001GenRad1972-96001GenRad1972-96001EPAC60/10 LN1EPAC60/10 LN1EPAC60/10 LN1EPAC60/10 LN1EPAC60/10 LN1uel & Kjaer22301TEACRD-130TE1SONYTCD-D71	1683358
	M5	Bruel & Kjaer		1329799
	M6	Bruel & Kjaer	4155	1769646
	M7	Bruel & Kjaer	TURER MODEL S Ljaer 4155 1 Ljaer 1972-9600 1 Ljaer 60/10 LN 1 Ljaer 60/10 LN 1 Ljaer 60/10 LN 1 Ljaer 2230 1 Ljaer 2230 1 Ljaer	1675641
	PA1	GenRad	1972-9600	DA1S
	PA2	GenRad	1972-9600	DA2
Pre-Amplifier	PA3	GenRad	1972-9600	DA3
	PA4	GenRad	1972-9600	DA4
	PA5	GenRad	1972-9600	DA5
	PA6	GenRad	1972-9600	DA6
	A1	EPAC 60/10 LN		0A
	A2	EPAC 60/10 LN		68
Amplifier	A3	EPAC	60/10 LN	69
Ampinter	A4	EPAC	60/10 LN	114
	A5	EPAC	60/10 LN	115
	A6	Bruel & Kjaer	2230	1082914
	T1	TEAC	RD-130TE	512546
Tape Recorder	T2	SONY	4155 4155 4155 4155 4155 4155 4155 4155 4155 4155 1972-9600 1972-9600 1972-9600 1972-9600 1972-9600 1972-9600 1972-9600 60/10 LN 60/10 LN 60/10 LN 60/10 LN 60/10 LN 60/10 LN 7000 1972-9600	67865
	C1	GenRad	1987	2894
Calibrator	C2	GenRad	1987	1096287007

Meas. Location		Code for Instrument Used*					
Site	Pos.**	Mic.	Pre-Amp.	Amp.	Tape Rec.	Cal.	
D	N1	M1	PA1		T1	C1	
	N2	M2	PA2		T1	C1	
	N3	M3	PA3	A1	T1	C1	
	N4	M4	PA4	A2	T1	C1	
	N1	M1	PA1	A1	T1	C1	
G	N2	M2	PA2	A2	T1	C1	
	N3	M3	PA3	A3	T1	C1	
	N1	M1	PA1	A1	T1	C1	
	N2	M2	PA2	A2	T1	C1	
ч	N3	M3	PA3	A3	T1	C 1	
11	N4	M4	PA4	A4	T1	C1	
	N5	M5	PA5		T2	C1	
	N6	M6	PA6		T2	C1	
	N1	M1	PA1	Al	T1	C1	
К	N2	M2	PA2	A2	T1	C1	
	N3	M3	PA3	A3	T1	· C1	
TGV H.P. Station	Northbound Platform	M7		A6	T2	C2	

TABLE 2. INSTRUMENTS USED FOR TRAIN NOISE MEASUREMENTS IN FRANCE

• See Table 1 for instrument code descriptions.

** See Figures 4, 6, 8, and 10 (A&B) for measurement positions at Sites D, G, H and K, respectively.

Meas. Location		Code for Instrument Used*						
Site	Pos.**	Mic.	Pre-Amp.	Amp.	Tape Rec.	Cal.		
	N1	M1	PA1		T1	C1		
2	N2	M2	PA2		T1	C1		
	N3	M3	PA3	A1	T1	C1		
	N4	M4	PA4	A2	T1	C1		
	N1	M1	PA1	A1	T1	C1		
3	N2	M2	PA2		T1	C1		
	N3	M3	PA3	A3	T1	C1		
	N4	M4	PA4	A4	T1	C1		
	N1	M1	PA1		T1	C1		
4	N2	M2	PA2		T1	C1		
	N3	M3	PA3	A1	T1	C1		
	N4	M4	PA4	A2	T1	C1		
Parma Station	Northbound Platform	M7		A6	T2	C2		

TABLE 3. INSTRUMENTS USED FOR TRAIN NOISE MEASUREMENTS IN ITALY

* See Table 1 for instrument code descriptions.

** See Figures 14, 16, and 18 (A&B) for measurement positions at Sites 2, 3 and 4, respectively.

TABLE 4	. INSTRUMENTS USED	FOR	TRAIN NOISE MEASUREMENTS IN SWEDEN
---------	--------------------	-----	------------------------------------

Meas. Location		Code for Instrument Used*					
Site	Pos.**	Mic.	Pre-Amp.	Amp.	Tape Rec.	Cal.	
	N1	M5	PA5	A1	T2	C1	
1	N2	M6	PA6	A5	T2	C1	
	N1	M1	PA1		T1	C1	
2	N2	M2	PA2	A2	T1	C1	
	N3	M3	PA3	A3	T1	C1	
	N4	M4	PA4	A4	T1	C1	
	N1	M1	PA1		T1	C1	
3A	N2	M2	PA2		T1	C1	
	N3	M3	PA3	A1	T1	C1	
	N4	M4	PA4	A2	T1	C1	
	N1	M1	PA1		T1	C1	
4	N2	M2	PA2		T1	C1	
	N3	M3	PA3	A1	T1	C1	
	N4	M4	PA4	A2	T1	C1	
	N1	M1	PA1		T1	C1	
5	N2	M2	PA2		T1	C1	
	N3	M3	PA3	A1	T1	C1	
	N4	M4	PA4	A2	T1	C1	

• See Table 1 for instrument code descriptions.

** See Figures 24, 26, 28, 32 and 34 (A&B) for measurement positions at Sites 1, 2, 3A, 4 and 5, respectively.

2.2 Ground Vibration Measurements

All ground vibration measurements were made using high-sensitivity accelerometers as vibration transducers, each with their own power supply. All accelerometers were oriented to measure vibration in the vertical direction. For measurements on soil, the accelerometers were mounted on top of ground-driven stakes using putty to secure them to the top plates of the stakes. For measurements on asphalt, the accelerometers were mounted directly to the asphalt surface using putty.

The accelerometer signals were amplified using low-noise amplifiers, and recorded on an 8-channel digital audio tape (DAT) recorder for subsequent laboratory analysis. The amplifiers were set for optimum signal-to-noise ratio, and the amplifier and tape recorder gain settings were recorded on field data sheets and voice annotated on the tapes. A 1-Volt peak reference signal at a fixed frequency of 1000 Hz, generated by the tape recorder, was recorded on each tape for calibration of the system, based on the specific sensitivities of the accelerometers.

Train speeds were measured using a radar speed detector, and each train event was also documented on videotape to provide a record of specific train consist details. Additional documentation was provided on field data sheets and by voice annotations on the audio and video recordings.

A list of the field instrumentation, including manufacturers, models and serial numbers, is provided in Table 5. Tables 6, 7 and 8 indicate the specific instrumentation used in France, Italy and Sweden, respectively, at each measurement site and position, referenced to the equipment codes in Table 5.

EQUIPMENT TYPE	EQUIPMENT CODE	MANUFACTURER	MODEL	SERIAL NUMBER
	AC1	РСВ	393B	162
Accelerameter	AC2	РСВ	393C	2480
	AC3	PCB	393C	2481
Acceleroineter	AC4	РСВ	393C	2482
	AC5	PCB 3930	393C	2876
	AC6	РСВ	293C	3179
	PS1	РСВ	480C06	1550
	PS2	РСВ	480E09	18974
Power	PS3	РСВ	480E09	18975
Supply	PS4	РСВ	480C02	2366
	PS5	PCB	480C02	2367
	PS6	РСВ	480C02	2368
	A2	EPAC	60/10 LN	68
Amplifier	A3	EPAC	60/10 LN	69
	A4	EPAC	60/10 LN	114
	A5	EPAC	60/10 LN	115
Tape Recorder	T3	TEAC	RD-130TE	723965

TABLE 5. FIELD INSTRUMENTS USED FOR GROUND VIBRATION MEASUREMENTS

TABLE 6. INSTRUMENTS USED FOR VIBRATION MEASUREMENTS IN FRANCE

Meas. I	ocation	Code for Instrument Used*					
Site	Pos.**	Accel.	Pwr. Supply	Amplifier	Tape Rec.		
	V1	AC1	PS1		T3		
D	V2	AC2	PS2		T3		
	V3	AC3	PS3		T3		
	V4	AC4	PS4	A4	T3		
	V5	AC5	PS5	A5	T3		
	V6	AC6	PS6	A3	T3		
	V1	AC2	PS2	A4	T3		
K	V2	AC3	PS3	A5	T3		

See Table 5 for instrument code descriptions.

.

** See Figures 4 and 10 (A&B) for measurement positions at Sites D and K, respectively.

Meas. J	Location	Code for Instrument Used*				
Site	Pos.**	Accel.	Pwr. Supply	Amplifier	Tape Rec.	
	V1	AC2	PS	2	T3	
2	V2	AC3	PS	3	T3	
	V3	AC4	PS4	A3	T3	
	V4	AC5	PS5	A4	Т3	
	V1	AC2	PS2		T3	
3	V2	AC3	PS3		Т3	
	V3	AC4	PS4	A2	T3	
	V4	AC5	PS5	A5	Т3	
	V1	AC1	PS1		T3	
	V2	AC2	PS2		Т3	
4	V3	AC3	PS3		T3	
4	V4	AC4	PS4	A3	T3	
	V5	AC5	PS5	A4	Т3	
	V6	AC6	PS6	A5	T3	

TABLE 7. INSTRUMENTS USED FOR VIBRATION MEASUREMENTS IN ITALY

* See Table 5 for instrument code descriptions.

** See Figures 14, 16, and 18 (A&B) for measurement positions at Sites 2, 3 and 4, respectively.

Meas. I	ocation	Code for Instrument Used				
Site	Pos.**	Accel.	el. Pwr. Supply Amplifier		Tape Rec.	
	V1	AC1	PS	1	Т3	
	V2	AC2	PS	2	Т3	
20	V3	AC3	PS	3	Т3	
מנ	V4	AC4	PS4	A3	Т3	
	V5	AC5	PS5	A4	T3	
	V6	AC6	PS6	A5	Т3	
	V1	AC5	PS5	A4	T3	
4	V2	AC6	PS6	A5	T3	
	V1	AC2	PS	52	T3	
5	V2	AC3	PS3	A3	T3	
	V3	AC4	PS4	A4	Т3	
	V4	AC5	PS5	A5	Т3	

TABLE 8. INSTRUMENTS USED FOR VIBRATION MEASUREMENTS IN SWEDEN

• See Table 5 for instrument code descriptions.

* See Figures 30, 32 and 34 (A&B) for measurement positions at Sites 3B, 4 and 5, respectively.

2.3 Vibration Propagation Tests

One of the key factors in projections of ground-borne vibration is how local geologic conditions will affect the propagation of vibration energy from the track support system to the foundations of adjacent buildings. Experience has shown that using standard geologic descriptors is rarely sufficient to define propagation characteristics. Therefore, tests were performed at the primary site in each of the three countries where high-speed train noise and vibration measurements were carried out. These included Site D in France, Site 4 in Italy and Site 3B in Sweden. The purpose of these tests was to obtain propagation data that could be used to normalize the ground-borne vibration measurement results by eliminating site-specific variables so that the vibration emission characteristics of the different types of high-speed trains could be compared on an equal basis.

The vibration propagation test procedure is illustrated in Figure 35. It basically consists of dropping a heavy weight on the ground and measuring the resulting vibration pulses at various distances from the impact. The force was measured using a Sensotec Model 41/574-03 load cell (Serial No. 286906). mounted on the ground below the weight. The force was applied to the ground at a series of points along a line running parallel to the railroad line, as close as possible to the tracks, as described in Section 1. The resulting vibration pulses were measured using accelerometers as described in Section 2.2, positioned along a line perpendicular to the tracks and bisecting the impact line as described in Section 1. Both the impact force and the vibration pulses were recorded using an instrumentation tape recorder as described in Section 2.2, for subsequent laboratory analysis. The relationship between the force caused by dropping the weight and the vibration pulse is called the transfer mobility.



FIGURE 35. GROUND-BORNE VIBRATION PROPAGATION TEST PROCEDURE

3. NOISE MEASUREMENT RESULTS

3.1 Noise Data Analysis Procedures

Analysis of the field data was carried out in the HMMH laboratory. For this analysis, the A-weighted maximum noise level (L_{Smax}) and Sound Exposure Level (SEL) for each train event were obtained directly from the tape-recorded data using a B&K Type 2230 sound level meter set at "slow" response. At the same time, a Rion Model LR-04 graphic level recorder, set at the "fast" writing speed, was used to obtain time-history graphs of each train event as well as the L_{Fmax} . The maximum noise level obtained using the "slow" averaging time (L_{Smax}) is better correlated with the SEL and is more appropriate for modelling train noise mathematically. However, the maximum noise level obtained using the "fast" averaging time (L_{Fmax}) is required to evaluate compliance with the U.S. Federal Railroad Noise Emission Standards.

Frequency analysis was carried out for selected recorded events, using multi-channel FFT spectrum analyzers to obtain one-third octave band sound pressure level spectra, averaged over intervals of maximum event noise levels. First, the noise signals were fed into the narrow-band analyzers at a maximum sampling rate for 20 kHz input bandwidth, and post-processing software was used to combine the narrow-band results into one-third octave noise spectra.

3.2 A-Weighted Train Noise Levels

The results of the wayside noise measurements are listed in Appendix A in terms of the following A-weighted noise level descriptors: L_{Smax} , L_{Fmax} and SEL. These results are given at each measurement position for each train event at each site, along with the measurement date and time, train type and length, and train speed.

To provide an overview of the results, representative European high-speed train noise levels at a variety of speeds are plotted in Figures 36 and 37. Figure 36 provides a graph of L_{Smax} as a function of train speed, normalized to a reference distance of 100 feet (30.5 meters). This normalization was based on interpolation between the measurement data obtained at 25 and 50 meters from the near track center line for the microphones located 1.5 meters above the ground. Figure 37 provides similar results in terms of SEL, with the data normalized to a reference distance of 100 feet and to a reference train length of 740 feet. Also shown on these graphs are train noise level versus speed curves generated by the noise model recently developed as part of the U.S. Northeast Corridor Project. These model curves are based on measurements conducted in the U.S. for several newer-technology trainsets including the German ICE, Swedish X2000 and the U.S./French RTL-2 Turboliner.

The results in Figures 36 and 37 indicate that the European train measurement data generally fall within the range of the train noise curves developed for the Northeast Corridor Project. The results also suggest that the TGV trains are typically the quietest of the trains tested in Europe, with noise emissions similar to the ICE and RTL-2 trains tested in the U.S. Wayside noise levels for the X2000 and Pendolino trains averaged about 5 decibels higher, with noise emissions similar to the X2000 train tested in the U.S. The data for the Eurostar trains showed the greatest variation, with noise levels scattered over the range for the other trains. However, we understand that there are two versions of the Eurostar trains currently in operation, and that this may account for the wide spread in the noise data for this equipment.

Other observations based on the A-weighted noise data are as follows:

- Regarding maximum wayside noise levels, the L_{Fmax} were generally 1-2 decibels above the L_{Smax} , with greater differences for measurements made closer to the track and for higher-speed trains.
- The noise levels measured at the high microphone position averaged about 1 decibel greater than the noise levels measured at the low microphone position at 25 meters from the near track.
- The measurements at French Site H indicated that the 3-meter high noise barrier at this site provided an insertion loss ranging from about 6 decibels at 50 meters from the near track to about 9 decibels at 25 meters from the near track, at a 1.5 meter-high receiver position.
- Although the higher speed French trains appeared to generate additional low-frequency noise of an aerodynamic nature, this noise did not appear to significantly affect the A-weighted noise levels for trains at speeds up to nearly 300 kph (186 mph). This observation is supported by Figures 36 and 37 which show that the higher speed noise data follow the noise model curves previously developed based on lower-speed noise measurements for the Northeast Corridor Project.

Finally, the results suggest that the trains measured in Europe would generally be expected to comply with the U.S. Federal Railroad Noise Emission Standard. The relevant standard for the operation of such trains is a L_{Fmax} of 93 dBA, with a 2-decibel tolerance, yielding an absolute limit of 95 dBA. Based on the measurement data, this corresponds to a limit of 93 dBA in terms of L_{Smax} . Of the representative data shown in Figure 36, only one Eurostar train exceeds this limit.

3.3 Train Noise Spectral Analysis

Noise spectra for selected train events are included in Appendix B.


Comparison with NEC Noise Models Lmax (slow) normalized to 100 ft dist.

FIGURE 36. HIGH-SPEED TRAIN MAXIMUM NOISE LEVEL VS. SPEED



Comparison with NEC Noise Models SEL normalized to 100 ft distance

FIGURE 37. HIGH-SPEED TRAIN SOUND EXPOSURE LEVEL VS. SPEED

4. GROUND-BORNE VIBRATION MEASUREMENT RESULTS

4.1 Vibration Data Analysis Procedures

Analysis of the field data was carried out in the HMMH laboratory. The recorded acceleration signals were integrated to obtain vibration velocity, using a B&K Model 2635 amplifier and signal conditioner. The resulting signals were fed into a Rion Model LR-04 graphic level recorder to obtain strip charts of the root mean square (RMS) vibration velocity as a function of time. The RMS time constant on the level recorder was set for one second, which is equivalent to the "slow" response setting on a standard sound level meter, and the maximum vibration level for each train event was read from the strip charts. Although experience suggests that the RMS vibration velocity level correlates best with human response to vibration, the peak velocity is often measured by geotechnical engineers to evaluate structural effects on buildings. Therefore, a B&K Type 2230 sound level meter was used in parallel with the graphic level recorder to obtain peak velocity data.

Frequency analysis was carried out for selected events, using multi-channel FFT spectrum analyzers to obtain one-third octave band spectra averaged over intervals of maximum vibration levels for each event. The acceleration signals were fed into the narrow-band analyzers set up for 500 Hz input bandwidth, and post-processing software was used to integrate the narrow-band data and combine the narrow-band results into one-third octave band vibration velocity spectra.

4.2 Overall Train Vibration Velocity Levels

The results of the ground vibration measurements are listed in Appendix C in terms of vibration velocity level expressed in decibels (VdB) relative to one micro-inch per second. Maximum vibration velocity levels are provided in terms of both RMS velocity (RMSV) and peak particle velocity (PPV), all in the vertical direction. These results are given at each measurement position for each train event at each site, along with the measurement date and time, train type and length, and train speed.

To provide an overview of the results, representative European high-speed train RMS vibration velocity levels are plotted in Figure 38. These levels are plotted as a function of distance, and have been normalized to a reference speed of 90 mph, assuming that ground-borne vibration varies proportional to 20 times the common logarithm of train speed. Also shown in this figure are best-fit vibration level vs. distance curves developed from measurements conducted in the U.S. for several newer-technology trainsets including the German ICE, Swedish X2000 and the U.S./French RTL-2 Turboliner.

The results in Figure 38 indicate that the TGV and Eurostar trains generated nearly identical ground vibration levels at the same site (French Site D). These levels were roughly 10 decibels lower than measured in the U.S. for the X2000 and RTL-2 trainsets, which generated the lowest ground vibration levels of the trains tested at the Northeast Corridor site. Furthermore, the vibration attenuation rate with distance at the French site was similar to that for the Northeast Corridor site. Figure 38 also shows that the ground vibration levels for Pendolino operation at Site 4 in Italy were all below the vibration levels measured for the trains in the U.S. However, the attenuation rate with distance at the Pendolino site appears to be more gradual at greater distances from the track. The highest ground vibration levels were generated by the X2000 trains at Site 3B in Sweden. At a distance of 100 feet, the levels are comparable to those measured for the X2000 in the U.S., but there appears to be very little attenuation with distance.

Due to the significant effects of ground composition on wayside train vibration levels, it is difficult to interpret the results in Figure 38, given the site variables involved. To be able to compare the results for the different sites, it is necessary to examine the results of the vibration propagation tests. These results are described below in Section 5.

.

4.3 Ground-Borne Train Vibration Spectral Analysis

.

Ground-borne vibration spectra for selected train events are included in Appendix D.



Comparison with NEC Vibration Models Normalized to 90 mph

FIGURE 38. HIGH-SPEED TRAIN VIBRATION LEVELS VS. DISTANCE

5. GROUND-BORNE VIBRATION PROPAGATION TEST RESULTS

5.1 Test Analysis Procedures

The steps used to analyze the train vibration and transfer mobility data to derive force densities were:

- 1. A narrowband spectrum analyzer was used to obtain transfer functions for each transfer mobility test and 1/3 octave band spectra for each train passby.
- 2. The narrowband transfer mobility spectra were used to calculate equivalent 1/3 octave band transfer mobilities.
- 3. The point-source transfer mobilities for each test site accelerometer were combined to approximate line-source transfer mobility.
- 4. The 1/3 octave bands for both the train and the propagation measurements were used to obtain best-fit curves of level vs. distance for each 1/3 octave band. These curves result in approximate line-source transfer mobility and train vibration spectra as a function of distance from the source.
- 5. The difference between the 1/3 octave band spectrum for train vibration and the transfer mobility at the same distance is the force density. The force density should not be a function of distance. In practice, force density was calculated at each measurement distance, and the average force density was used to characterize each type of trainset. For all of the trainsets, the force densities at the six measurement distances were well clustered around the average. The typical range between the highest and lowest was 3 to 4 decibels.

The end result of the analysis was a force density to characterize each type of trainset, line-source transfer mobility functions characterizing each of the primary test sites, and the trainset 1/3 octave band ground-borne vibration as a function of distance.

5.2 Summary of Test Results

As suggested by the results in Section 4.2, it is likely that much of the difference in ground-borne vibration between the trainsets is due to geology rather than differences in suspensions or wheel conditions of the trainsets. The line source transfer mobility spectra for the three different measurement sites are shown in Figure 39. The transfer mobilities are very different. For example, at 100 Hz the transfer mobility at Site 3B in Sweden is 8 decibels higher than at Site D in France and about 30 decibels higher than at Site 4 in Italy. All of the sites were in rural areas where relatively little is known about the specific geology at the test sites. These differences in transfer mobility are fairly consistent out to 100 meters from the vibration source.

The force density functions derived for X2000, Pendolino, TGV, and Eurostar trainsets, all normalized to a speed of 150 mph are shown in Figure 40. The force densities are very different, but the differences are not as large as the differences in the measured vibration levels. The TGV and Eurostar force densities are close enough to be considered the same. The X2000 and the Pendolino are surprisingly similar considering the large difference in the vibration spectra.

European High-Speed Rail Noise and Vibration Measurements	Page 75
HMMH Report No. 293630-2	April 1996

The four force density functions can be combined with the transfer mobility from one site to approximate what the vibration levels would be if all of the trainsets were operating on the same track. The resulting overall vibration levels using the transfer mobility from Site D in France are shown in Figure 41 and the same results using the transfer mobility from site 3B in Sweden are shown in Figure 42. Both figures show that using the same transfer mobility substantially reduces differences in the overall vibration levels. With the transfer mobility from Sweden, the TGV, Eurostar, and X2000 are all within about 2 decibels, and the Pendolino is 3 to 4 decibels lower. In this case, ground-borne vibration from the different trainsets is between 75 and 80 VdB at 30 meters from the track. With the transfer mobility from France, the TGV and Eurostar are 2 to 3 decibels lower than the Pendolino and the X2000 is about 4 decibels higher than the Pendolino. The levels are between 65 and 73 at 30 meters from the track centerline. The overall conclusion is that all of the trains would have significantly higher vibration levels at the Swedish test site than at the French site.

To further illustrate the strong effects of the transfer mobility, Figure 43 shows vibration level vs. distance applying the X2000 force density to the three transfer mobility functions. This shows that close to the trade centerline, the projected vibration levels are all relatively high. However, the levels with the transfer mobility from Site 3B in Sweden show considerably slower attenuation with distance than with the other two transfer mobilities.



Comparison of Transfer Mobility 100 feet from track centerline

FIGURE 39. LINE-SOURCE TRANSFER MOBILITY AT THE TEST SITES



Force Densities, 150 mph Eurpoean Measurements, 5/95

FIGURE 40. NORMALIZED TRAINSET FORCE DENSITY FUNCTIONS



Using transfer mobility from Site D in France Train Speed 150 mph

FIGURE 41. PROJECTED VIBRATION - SITE D (FRANCE) TRANSFER MOBILITY



Ground-borne Vibration vs Distance Velocity Level Projected using Measured Force Densities and Transfer Mobility

Train Speed 150 mph

FIGURE 42. PROJECTED VIBRATION - SITE 3B (SWEDEN) TRANSFER MOBILITY



FIGURE 43. PROJECTED VIBRATION VELOCITY USING X2000 FORCE DENSITY

.

-

APPENDIX A: A-WEIGHTED TRAIN NOISE MEASUREMENT DATA

HIGH-SPEED TRAIN NOISE DATA: FRANCE - SITE D (PRIMARY SITE) - MAY 10, 1995

EVE	TIME	TRAIN D	ESCR	IPTION					MEAS	JRED A-WE	EIGHTEI	D SOUND L	EVEL (dBA	.)			
NO.	OF DA	Туре	Dir.	Length	Speed	Ch1(25mS	B/29.5mNE	¥1.5mH)	Ch2(25mS	B/29.5mNB	V4.0mH)	Ch3(50mS	B/54.5mNB	(1.5mH)	Ch4(75mS	B/79.5mNE	V1.5mH)
				(m)	(kpt.)	Lmax(s)	Lmax(f)	SEL	Lmax(s)	Lmax(f)	SEL	Lmax(s)	Lmax(f)	SEL	Lmax(s)	Lmax(f)	SEL
1	12:18	TGV	NB	237.5	290	86.8	89.1	97.2	89.6	89.4	93.8	88.5	85.0	96.9	82.5	83.0	87.8
3	12:54	TGV-2	NB	475.0	294	88.2	89.6	100.5	89.7	91.3	96.0	85.6	87.0	92.0	84.5	85.0	91.6
4	12:58	TGV	SB	237.5	290	93.1	95.7	97.6	92.7	96.0	97.8	88.5	90.3	94.4	87.7	88.7	93.4
5	13:10	TGV	SB	237.5	293	92.6	95.2	97.5	92.2	95.0	97.2	88.4	89.6	94.3	87.1	88.3	93.3
6	13:15	TGV	SB	237.5	296	96.2	99.3	101.2	95.4	98.9	100.5	92.2	94.0	97.9	91.7	93.1	97.4
7	13:17	TGV	NB	237.5	293	87.1	89.1	91.8	88.4	91.5	93.7	84.3	85.2	90.0	83.3	84.2	89.3
8	16:25	TGV	SB	237.5	296	93.0	94.7	96.8	92.3	94.0	96.4	88.6	89.0	93.5	87.1	87.8	92.5
9	16:33	Eurostar	SB	393.7	269	93.9	97.1	99.8	93.6	96.8	100.3	90.2	91.8	96.7	88.6	89.8	95.6
10	16:40	TGV	NB	237.5	294	89.4	92.2	94.5	91.0	92.7	95.8	86.5	87.1	92.0	85.6	86.2	90.6
11	16:44	TGV	SB	237.5	290	91.4	92.3	95.5	90.7	91.5	95.4	87.3	87.9	92.0	85.9	86.8	90.5
12	16:51	IGV-2	SB	475.0	293	93.0	93.7	99.3	92.3	93.1	98.9	88.7	89.7	95.4	86.9	87.3	94.1
13	17:30	Eurostar	NB	393.7	293	89.3	91.8	95.3	90.3	93.1	97.2	85.8	88.0	92.8	83.9	86.1	91.3
14	17:31	Eurostar	SB	393.7	296	99.5	102.6	104.4	98.4	101.9		94.8	97.1		93.4	96.1	
15	17:35	TGV	NB	237.5	286	87.4	89.5	92.5	89.6	92.2	94.9	84.4	86.1	90.2	82.5	83.5	88.5
16	17:39	TGV	NB	237.5	200	85.6	86.6	90.5	86.9	88.0	91.2	82.1	83.2	97.8	81.1	81.9	86.6
1/	17:43	IGV	SB	237.5	294	92.7	94.9	96.8	91.9	94.6	96.8	87.8	89.0	93.3	85.1	86.7	92.1
10	17.52	TGV		237.5	290	67.5	89.9	92.8	89.7	91.0	94.6	64.0	85.5	90.5	02.7	63.4	66.5
19	18:06	TGV	NB	237.5	283	91.3	95.2	93.9	95.0	100.0	97.4	91.0	94.2	94.0	92.1	96.0	94.8
20	18.10	TGV	NB	237.5	293	80.0	95.5	97.2	92.7	95.0	97.1	86.5	88.0	01.8	85.0	88.1	92.9
20	10.10	TOV	CD	207.5	204	03.2	02.1	07.0	01.7	020	06.5	00.0	89.7	02.5	96.5	97.1	30.0 02.0
23	18:30	TGV	SB	237.5	293	95.5	99.0	100.1	94.5	98.0	99.3	91.1	92.2	96.5	89.7	90.9	95.2
25	18:42	TGV	NB	237.5	296	87.7	89.7	92.8	89.1	90.0	04.2	85.0	85.5	00.8	83.1	83.7	89.3
26	18:44	TGV	SB	237.5	296	95.9	99.0	99.8	95.5	98.2	99.5	92.8	96.5	96.6	91.2	94.2	95.0
AVG	i	TGV	SB	237.5	294	93.6	95.9	98.0	93.0	95.4	97.7	89.4	90.7	94.6	87.9	89.2	93.4
			NB	237.5	289	88.0	90.3	93.4	90.0	92.1	94.6	85.9	86.6	92.7	84.3	85.6	89.6
AVG	i	TGV-2	SB	475.0	293	93.0	93.7	99.3	92.3	93.1	98.9	88.7	89.7	95.4	86.9	87.3	94.1
			NB	475.0	294	88.2	89.6	100.5	89.7	91.3	96.0	85.6	87.0	92.0	84.5	85.0	91.6
A.V/C		C. reat-	60	2027	000	00.7	00.0	100 4	00.0	00.4	00.0	00.5	04.5	01.0	01.0	02.0	80.0
AVC	L	Eurostar	NB	393.7	283	90.7 89.3	99.9 91.8	95.3	90.0	99.4	90.8	92.5	94.5 88.0	88.0	83.9	93.0 86.1	86.1

•

HIGH-SPEED TRAIN NOISE DATA: FRANCE - SITE G (CUT SITE) - MAY 9, 1995

EVE	TIME	TRAIN D	ESCF	IPTION					MEAS	URED A-W	EIGHTE	ED SOUND	LEVEL (d	BA)
NO.	OF D	Туре	Dir.	Lengt	Speed	Ch1(44mS	SB/48.5mNI	3/1.5m	Ch2(44m5	B/48.5mN	B/4.0m	Ch3(75mS	SB/79.5mNE	3/1.5m
				(m)	(kph)	Lmax(s)	Lmax(f)	SEL	Lmax(s)	Lmax(f)	SEL	Lmax(s)	Lmax(f)	SEL
8	16:34	Eurostar	SB	393.7	257	76.5	78.4	84.2				64.6	68.0	72.0
10	16:41	TGV	NB	237.5	293	77.7	78.9	83.2				60.3	61.5	67.9
11	16:44	TGV-2	SB	475.0	285	76.8	78.3	83.1				60.6	61.3	69.3
12	16:50	TGV-2	SB	475.0	290	78.5	79.1	89.6				65.8	68.2	73.0
13	16:56	TGV	SB	237.5	294	77.8	80.0	83.4				61.3	62.1	68.2
15	17:01	TGV	SB	237.5	154	66.5	67.0	74.2						
17	17:24	TGV	NB	237.5	291	77.8	79.7	84.2	90.8	92.9		61.2	62.0	70.1
18	17:28	Eurostar	NB	393.7	264	77.4	79.0	85.5	87.8	90.0	95.7	60.0	61.3	68.8
20	17:38	TGV	NB	237.5	293	76.5	77.2	81.9	87.0	88.1	92.5	59.9	61.3	70.8
21	17:43	TGV	SB	237.5	291	79.1	79.9	84.3	86.2	87.8	92.4	66.3	67.9	72.3
22	17:51	TGV	NB	237.5	288	79.5	80.2	84.8	87.3	88.3	92.9	61.3	62.3	70.7
23	18:03	TGV	NB	237.5	294	81.7	83.1	86.4	90.4	92.1	97.8	64.6	66.2	71.8
24	18:07	TGV	SB	237.5	291	77.9	79.0	83.0	87.0	88.0	92.5	68.0	73.0	74.1
25	18:13	TGV	SB	237.5	288	74.6	75.0	80.3	87.7	88.5	92.8	61.6	63.0	68.6
26	18:16	TGV-2	NB	475.0	294	79.1	80.8	89.0	89.3	90.0	96.2	63.4	64.5	72.1
27	18:31	TGV	SB	237.5	267	75.9	77.7	81.7	85.8	87.0	91.4	63.0	65.8	70.8
28	18:38	Eurostar	NB	393.7	286	78.9	79.1	86.3	88.2	89.8	95.7	62.6	63.2	71.3
29	18:41	TGV	NB	237.5	270	79.9	81.5	84.9	86.6	87.8	92.1	61.3	62.1	69.4
30	18:42	TGV	SB	237.5	288	78.5	79.7	83.7	86.2	86.9	91.7	66.4	69.5	73.0
31	19:05	TGV	NB	237.5	293	81.1	82.4	86.1	88.4	90.3	93.3	65.1	66.3	71.9

HIGH-SPEED TRAIN NOISE DATA: FRANCE - SITE H (BARRIER SITE) - MAY 11, 1995

EVE	TIME	TRAIN D	ESCR	IPTION				MEA	SURED A-	WEIGHTED	SOUNE	LEVELBE	HIND BAR	RIER (de	BA)		
NO.	OF DA	Туре	Dir.	Length	Speed	Ch1(25mN	B/29.5mSE	¥1.5mH)	Ch2(25mN	B/29.5mSB	V4.0mH)	Ch3(50mN	B/54.5mSB	1.5mH)	Ch4(75ml	IB/79.5mSB	/1.5m⊢`
				(m)	(kph)	Lmax(s)	Lmax(f)	SEL	Lmax(s)	Lmax(I)	SEL	Lmax(s)	Lmax(f)	SEL	Lmax(s)	Lmax(f)	SEL
28	11:09	TGV	SB	237.5		76.5	78.4	81.7	78.9	81.1	84.1	77.3	78.5	83.6	75.8	76.7	82.ĉ
29	11:18	TGV	NB	237.5	_	83.1	84.8	88.3	83.7	85.5	89.0	82.7	85.2	88.4	81.3	83.1	87.C
30	11:25	TGV	NB	237.5	290	82.7	84.3	87.4	83.1	85.0	88.3	82.9	84.9	88.3	81.3	82.8	87.2
31	11:27	Eurostar	SB	393.7	267	77.2	79.0	84.4	77.9	81.0	86.1	78.4	79.8	85.3	76.1	78.1	84.E
32	11:35	TGV-2	NB	475.0	294	84.3	86.1	90.7	84.9	86.8	91.3	85.0	87.3	90.9	83.2	85.0	90.C
33	11:40	TGV	SB	237.5	294	75.9	77.6	81.7	78.5	80.0	84.2	77.4	79.0	84.1	76.6	78.0	83.C
34	11:42	TGV	SB	237.5	298	78.4	80.2	83.2	80.7	82.7	85.6	78.8	80.0	84.9	77.5	79.7	84.C
35	12:02	Eurostar	SB	393.7	283	78.3	80.3	85.4	80.3	82.6	87.5	77.2	79.6	85.4	76.5	78.1	84.4
37	12:11	TGV	NB	237.5	294	83.5	85.0	88.4	84.4	85.8	89.4	82.3	83.1	88.1	81.5	83.0	87.7
38	12:18	TGV	NB	237.5	293	82.9	84.4	87.6	83.3	85.0	88.2	81.3	82.2	87.2	79.5	80.6	88.4
39	12:32	Eurostar	NB	393.7	296	85.3	88.4	91.4	85.9	89.1	92.5	84.7	87.2	91.8	82.4	84.2	90.0
40	12:54	TGV-2	NB	475.0	294	85.0	87.0	91.1	86.0	88.1	92.0	84.2	85.7	90.7	82.5	83.2	89.E
41	13:08	TGV	SB	237.5	298	78.4	79.6	83.8	80.4	81.9	85.9	78.5	80.0	85.1	78.7	80.3	85.1
42	13:14	TGV	SB	237.5	293	77.2	78.4	82.2	79.7	81.4	84.8	78.2	79.1	84.2	78.0	79.4	83.6
AVG		TGV	NB	237.5	292	83.0	84.6	87.8	83.6	85.3	88.6	82.2	83.4	87.9	80.8	82.1	87.E
			SB	237.5	296	77.5	79.0	82.7	79.8	81.5	85.1	78.2	79.5	84.6	77.7	79.4	83.9
AVG		TGV-2	NB	475.0	294	84.7	86.6	90.9	85.5	87.5	91.7	84.6	86.5	90.8	82.9	84.1	89.8
AVG		Eurostar	S8	393.7	275	77.8	79.7	84.9	79.1	81.8	86.8	77.8	79.7	85.4	76.3	78.1	84.5

HIGH-SPEED TRAIN NOISE DATA: FRANCE - SITE H (EMBANKMENT SITE) - MAY 11, 1995

EVE	TIME	TRAIN D	ESCR	IPTION		MEASURE	D A-WEIGH	TED SC	OUND LEVE	L - UNSHIE	LDED (
NO.	OF DA	Туре	Dir.	Length	Speed	LCh(25mN	B/29.5mSB/	1.5mH	RCh(50mN	B/54.5mSB	/1.5mH
				(m)	(kph)	Lmax(s)	Lmax(f)	SEL	Lmax(s)	Lmax(f)	SEL
3	11:25	TGV	NB	237.5	290	91.8	93.5	96.5	87.9	88.4	96.3
4	11:27	Eurostar	SB	393.7	267	86.2	88.9	97.9	82.7	85.0	90.3
5	11:40	TGV	SB	237.5	294	87.2	89.2	92.2	84.7	85.9	90.1
6	11:42	TGV	SB	237.5	298	87.2	89.0	92.1	85.3	86.1	90.3
7	12:02	Eurostar	SB	393.7	283	86.7	89.1	93.3	84.0	85.5	91.5
8	12:11	TGV	NB	237.5	294	94.0	96.0	98.7	90.7	92.9	95.8
9	12:18	TGV	NB	237.5	293	91.0	92.2	95.5	87.0	88.0	92.0
10	12:32	Eurostar	NB	393.7	296	92.5	96.0	99.1	88.6	90.8	96.1
11	12:55	TGV-2	NB	475.0	294	94.9	96.7	80.6	92.3	93.4	98.1
12	13:09	TGV	SB	237.5	298	87.8	90.0	92.9	86.8	88.0	92.0
13	13:13	TGV	SB	237.5	293	86.3	87.7	91.1	84.5	85.3	89.7
14	13:19	TGV	NB	237.5	294	90.9	93.0	95.9	88.0	88.7	93.5
AVG		TGV	NB	237.5	293	91.9	93.7	96.7	88.4	89.5	94.4
			SB	237.5	296	87.1	89.0	92.1	85.3	86.3	90.5
AVG		Eurostar	SB	393.7	275	86.5	89.0	95.6	83.4	85.3	90.9

HIGH-SPEED TRAIN NOISE DATA: FRANCE - SITE K (LOW-SPEED SITE) - MAY 11, 1995

EVE	TIME	TRAIN D	ESCF	IPTION					MEAS	JRED A-W	EIGHTE	ED SOUND	LEVEL (d	BA)
NO.	OF D	Туре	Dir.	Lengt	Speed	Ch1(25ml	NB/29.5mSI	3/1.5m	Ch2(25mN	IB/29.5mSE	3/4.0m	Ch3(50mh	NB/54.5mS	B/1.5m
				(m)	(kph)	Lmax(s)	Lmax(f)	SEL	Lmax(s)	Lmax(f)	SEL	Lmax(s)	Lmax(f)	SEL
48-1	16:30	TGV	SB	237.5	193	81.0	82.4	87.2	83.6	85.0	89.7	78.5	80.0	85.0
50-2	16:35	TGV	NB	237.5	198	88.2	89.5	93.5	88.2	89.7	93.9	85.0	86.0	90.8
51-3	16:40	Eurostar	SB	393.7	206	85.0	87.2	91.5	86.4	88.6	93.2	82.0	83.9	89.1
52-4	16:49	TGV	SB	237.5	201	80.3	81.0	86.0	83.3	84.4	88.9	78.2	78.6	84.3
53-5	16:52	TGV-2	SB	475.0	185	83.0	84.9	89.3	85.7	87.3	92.1	80.7	82.2	87.6
53-7	17:25	Eurostar	NB	393.7	145	87.0	89.0	93.9	86.6	88.8	94.1	83.5	85.5	91.3
54-8	17:33	Eurostar	SB	393.7	169	88.3	90.1	93.9	90.8	92.9	96.5	86.9	88.5	92.5
55-9	17:36	TGV	NB	237.5	193	88.3	89.2	96.7	87.8	89.1	93.7	84.5	86.3	90.5
55-1	17:45	TGV	NB	237.5	198	88.3	89.9	93.9	88.6	89.9	94.2	85.4	86.1	91.3
56-1	17:50	TGV	SB	237.5	201	82.5	83.1	88.7	85.4	87.0	91.5	81.1	82.6	87.4
56-1	18:02	TGV	NB	237.5	196	88.6	90.9	94.6	88.8	90.0	94.5	86.1	88.0	91.8
57-1	18:12	TGV	SB	237.5	182	81.7	83.2	87.5	83.8	85.3	89.9	78.9	80.1	85.7
57-1	18:30	Eurostar	NB	393.7	169	87.2	89.0	94.1	87.3	89.0	94.7	84.2	86.0	91.9
58-1	18:33	TGV	NB	237.5	216	87.1	89.0	92.7	87.4	88.5	93.1	84.4	85.6	90.2
58-1	19:00	TGV	NB	237.5	166	85.0	87.8	91.4	85.6	88.0	92.0	81.4	83.3	88.4
AVG		TGV	NB	237.5	195	87.6	89.4	93.8	87.7	89.2	93.6	84.5	85.9	90.5
			SB	237.5	194	81.4	82.4	87.4	84.0	85.4	90.0	79.2	80.3	85.6
AVG		Eurostar	NB	393.7	157	87.1	89.0	94.0	87.0	88.9	94.4	83.9	85.8	91.6
			SB	393.7	188	86.7	88.7	92.7	88.6	90.8	94.9	84.5	86.2	90.8

HIGH-SPEED TRAIN NOISE DATA: FRANCE - TGV HAUTE PICARDIE STA (NB PLATFORM) MAY 12, 1995

TIME	TRAIN	DESCR	IPTION		MEASURE	D SOUND	LEVEL
OF D	Туре	Dir.	Lengt	Speed	LCh(15mN	NB/20mSB/	1.5mH)
			(m)	(kph)	Lmax(s)	Lmax(f)	SEL
18:00	TGV	SB			96.2	98.2	100.8
18:07	TGV	NB			100.6	103.1	106.6
18:14	TGV	SB			97.3	98.6	103.1
18:19	TGV	NB			98.1	101.0	102.5
18:22	TGV	NB			99.3	103.4	103.7
18:27	TGV	SB			95.3	97.0	99.9
	TIME OF D 18:00 18:07 18:14 18:19 18:22 18:27	TIME TRAIN OF D Type 18:00 TGV 18:07 TGV 18:14 TGV 18:19 TGV 18:22 TGV 18:27 TGV	TIMETRAIN DESCR TypeOF DType18:00TGVSB18:07TGVNB18:14TGVSB18:19TGVNB18:22TGVNB18:27TGVSB	TIME TRAIN DESCRIPTION OF D Type Dir. Lengt (m) 18:00 TGV SB 18:07 TGV NB 18:14 TGV SB 18:19 TGV NB 18:22 TGV NB 18:27 TGV SB	TIMETRAIN DESCRIPTIONOF DTypeDir.LengtSpeed (m)18:00TGVSB18:07TGVNB18:14TGVSB18:19TGVNB18:22TGVNB18:27TGVSB	TIMETRAIN DESCRIPTIONMEASUREOF DTypeDir.LengtSpeedLCh(15m)(m)(kph)Lmax(s)18:00TGVSB96.218:07TGVNB100.618:14TGVSB97.318:19TGVNB98.118:22TGVNB99.318:27TGVSB95.3	TIME TRAIN DESCRIPTION MEASURED SOUND OF D Type Dir. Lengt Speed LCh(15mNB/20mSB/ Lmax(s) Lmax(f) 18:00 TGV SB 96.2 98.2 18:07 TGV NB 100.6 103.1 18:14 TGV SB 97.3 98.6 18:19 TGV NB 98.1 101.0 18:22 TGV NB 99.3 103.4 18:27 TGV SB 95.3 97.0

HIGH-SPEED TRAIN NOISE DATA: ITALY - SITE 2 (AT-GRADE SITE) - MAY 15, 1995

EVE	TIME	TRAIN D	ESCR	IPTION					MEASU	JRED A-WE	EIGHTED	SOUND L	EVEL (dBA)			
NO.	OF DA	Туре	Dir.	Length	Speed	Ch1(25mN	B/28.7mSB	/1.5mH)	Ch2(25mN	IB/28.7mSB	V4.0mH)	Ch3(50mN	IB/53.7mSB	(1.5mH)	Ch4(75mN	IB/78.7mSB	(1.5mH)
				(m)	(kph)	Lmax(s)	Lmax(f)	SEL	Lmax(s)	Lmax(f)	SEL	Lmax(s)	Lmax(f)	SEL	Lmax(s)	Lmax(f)	SEL
76	20:19	Pendolino	NB	236.6	194	90.2	91.6	96.3		-	—	85.6	86.2	93.5	83.6	84.2	92.1
77	20:34	Pendolino	SB	236.6		86.3	87.5	92.6			-	83.0	83.8	89.5	81.2	82.0	87.9
80	20:49	Pendolino	SB	236.6	190		88.3			90.0		-	83.2	-	80.6	81.1	88.3

....

HIGH-SPEED TRAIN NOISE DATA: ITALY - SITE 3 (CURVE SITE) - MAY 17, 1995

EVE	TIME	TRAIN D	ESCR	IPTION					MEASL	JRED A-WE	IGHTE	SOUND L	EVEL (dBA	.)			
NO.	OF DA	Туре	Dir.	Length	Speed	Ch1(25mN	B/28.7mSB	V1.5mH)	Ch2(25mN	B/28.7mSB	/5.0mH)	Ch3(50mN	B/53.7mSB	(1.5mH)	Ch4(75ml	IB/78.7mSB	/1.5mH)
				(m)	(kph)	Lmax(s)	Lmax(f)	SEL	Lmax(s)	Lmax(f)	SEL	Lma::(s)	Lmax(f)	SEL	Lmax(s)	Lmax(f)	SEL
7	20:03	Pendolino	NB	236.6	132	84.7	86.0	92.0	85.9	87.0	93.4	84.7	83.1	93.7	90.3	90.8	97.8
11	20:36	Pendolino	SB	236.6	148	78.1	78.8	85.2	81.7	82.3	88.5	76.2	77.0	83.1	74.6	75.0	80.8
14	20:48	Pendolino	SB	236.6	130	76.2	77.0	83.5	79.3	80.1	86.6	74.6	75.2	82.0	72.6	73.0	80.1
16	20:54	Pendolino	NB	236.6	154	87.0	88.2	93.5	88.5	89.7	95.9	84.7	85.7	91.5	82.2	83.0	89.2

.~

HIGH-SPEED TRAIN NOISE DATA: ITALY - SITE 4 (PRIMARY SITE) - MAY 16 & 18, 1995

EVE	TIME	TRAIN D	ESCR	IPTION					MEAS	JRED A-WE	EIGHTED	SOUND L	EVEL (dBA	.)			
NO.	OF DA	Туре	Dir.	Length	Speed	Ch1(25mS	B/28.7mNE	V1.5mH)	Ch2(25mS	B/28.7mNE	V5.0mH)	Ch3(50mS	B/53.7mNB/	(1.5mH)	Ch4(75mS	B/78.7mN3	(1.5mH)
				(m)	(kph)	Lmax(s)	Lmax(f)	SEL	Lmax(s)	Lmax(f)	SEL	Lmax(s)	Lmax(f)	SEL	Lmax(s)	Lmax(f)	SEL
MAY	16, 1995	5															
91	8:58	Pendolino	SB	236.6	175	87.7	88.0	94.4	87.4	88.0	94.0	86.3	87.2	93.1	83.1	83.8	90.0
95	9:59	Pendolino	NB	236.6	190	88.4	89.3		91.3	93.0		87.2	88.4		81.6	82.4	_
99	14:02	Pendolino	SB	236.6	195	88.2	88.9	97.3	87.8	88.9	94.4	86.3	87.3	92.7	83.0	84.0	89.1
105	16:59	Pendolino	NB	236.6	193	85.9	87.0	92.4	87.3	87.4	93.6	84.3	86.0	90.7	81.1	81.8	87.8
MAY	18, 1995	5															
24	7:57	Pendolino	S8	236.6	182	89.9	90.8	95.2	89.3	90.8	94.8	87.4	89.0	92.9		82.8	-
27	8:59	Pendolino	SB	236.6	196	92.3	93.0	98.6	91.6	92.3	97.9	89.1	90.0	95.4	83.2	84.9	89.5
31	9:18	Pendolino	S8	236.6	185	88.4	89.2	94.3	88.1	89.5	94.2	85.3	86.8	91.4	79.8	81.0	86.2
36	10:00	Pendolino	NB	236.6	192	89.5	90.7	95.2	92.1	93.0	97.6	85.3	86.5	91.1	77.6	79.0	83.5
		Deedellas	C D	000 0	407	00.0	00.0	00.0	00.0	00.0	05.4	00.0	00.4	~ 1	00.0	00.0	
AVG		Pendolino	20	236.6	187	89.3	90.0	96.0	88.8	89.9	95.1	86.9	88.1	93.1	82.3	83.3	88.7
			NB	230.0	192	87.9	89.0	93.8	90.2	91.1	95.6	85.6	87.0	90.9	60.1	81.1	85.7

HIGH-SPEED TRAIN NOISE DATA: ITALY - PARMA STATION (NB PLATFORM) MAY 18, 1995

EVE	TIME	TRAIN DE	SCRIP	TION		MEASUF	RED SOUN	D LEVE	L(dB
NO.	OF D	Туре	Dir.	Lengt	Speed	LCh(4n	nNB/8mSB	/1.5mH)	
				(m)	(kph)	Lmax(s)	Lmax(f)	SEL	LEQ
1	19:54	Freight				99.6	102.0	111.1	
2	20:01	Inter-City	NB			103.4	104.8	110.4	
3	20:02	Freight	SB			99.5	100.2	109.6	
4	20:15	Loc.(IC)			0		87.5		85.0
5	20:19	Pendolino			0		83.0		77.0
6	20:22	Pendolino	SB			97.8	98.9	107.5	
7	20:32	Pendolino	SB			98.9	104.5	105.5	
8	20:56	Inter-City	SB			100.7	104.0	107.6	
9	20:57	Inter-City	NB			105.7	108.5	112.1	
10	21:04	Inter-City	SB			99.7	103.4	107.4	
11	21:06	Pendolino	NB			102.4	103.7	108.7	

HIGH-SPEED TRAIN NOISE DATA: SWEDEN - SITE 1 (EMBANKMENT SITE) - MAY 22, 1995

EVE	TIME	TRAIN D	ESCR	IPTION		MEASU	RED A-WE	IGHTED	SOUND LE	EVEL (dBA))
NO.	OF DA	Туре	Dir.	Length	Speed	LCh(25mE	B/29.5mWB	1.5mH	Ch2(50mEl	3/54.5mWB	/1.5mH
				(m)	(kph)	Lmax(s)	Lmax(f)	SEL	Lmax(s)	Lmax(f)	SEL
1	9:20	X2000	WB	140.0	164	79.6	81.5	84.2	83.4	86.0	88.2
3	9:42	X2000	WB	140.0	153	75.7	77.5	81.1	79.8	80.9	85.0
6	10:38	X2000	WB	140.0	177	81.5	84.5	85.2	84.3	86.3	88.9
9	11:31	X2000	EB	140.0	171	91.9	95.0	96.9	89.7	91.4	95.0
11	13:29	X2000	EB	140.0	169	91.7	94.8	96.0	88.1	90.1	93.0
13	13:53	X2000	WB	140.0	167	82.5	85.2	86.8	86.5	88.1	90.9
15	16:28	X2000	EB	140.0	177	85.3	89.4	89.9	82.4	85.0	87.8
17	16:47	X2000	WB	140.0	175	79.9	82.7	84.3	81.3	83.2	86.5
18	17:29	X2000	EB	140.0	177	89.9	94.5	94.7	86.7	89.1	92.1
19	18:29	X2000	EB	140.0	169	85.1	87.3	89.0	82.8	83.7	88.2
21	18:48	X2000	WB	140.0	171	82.7	84.2	87.2	86.1	88.1	90.2
AVG		X2000	EB	140.0	173	88.8	92.2	93.3	85.9	87.9	91.2
			WB	140.0	168	80.3	82.6	84.8	83.6	85.4	88.3

HIGH-SPEED TRAIN NOISE DATA: SWEDEN - SITE 2 (CUT SITE) - MAY 22, 1995

EVE	TIME	TRAIN [DESCR	PTION		MEASURED A-WEIGHTED SOUND LEVEL (dBA)											
NO.	OF DA	Туре	Dir.	Dir. Length	Speed	Ch1(20mE	B/24.5mW	3/1.5mH	I Ch2(40mEB/44.5mWB/1.5mH (Ch3(40mEB/44.5mWB/5.0mH			Ch4(65mEB/69.5mWB/1.5mH		
				(m)	(kph)	Lmax(s)	Lmax(f)	SEL	Lmax(s)	Lmax(f)	SEL	Lmax(s)	Lmax(f)	SEL	Lmax(s)	Lmax(f)	SEL
45	9:20	X2000	WB	140.0	164	92.2	93.6	101.5	76.1	77.0	82.1	84.6	85.8	90.3	69.7	70.2	76.9
46	9:42	X2000	WB	140.0	153	92.2	95.0	97.8	79.6	81.9	84.2	84.0	85.3	89.8	73.9	75.0	83.7
48	10:38	X2000	WB	140.0	177	93.1	94.5	98.3	75.8	76.9	81.6	84.8	85.7	90.0	70.6	71.9	77.1
51	11:31	X2000	EB	140.0	171	96.2	97.2	101.1	76.7	78.2	81.5	82.6	84.0	87.5	71.6	73.0	77.3
53	13:29	X2000	EB	140.0	169	96.0	97.0	100.8	76.5	78.0	81.2	82.0	83.9	87.0	70.9	72.0	77.0
55	13:53	X2000	WB	140.0	167	92.9	95.0	98.5	75.5	76.9	81.5	84.7	86.0	90.5	69.6	70.2	76.3
56	16:28	X2000	EB	140.0	177	96.2	97.5	100.6	76.4	77.2	81.6	82.5	83.8	87.4	71.1	71.9	76.8
58	16:47	X2000	WB	140.0	175	95.0	95.9	100.0	78.2	79.2	84.6	86.4	87.1	91.8	71.9	73.0	78.6
59	17:29	X2000	EB	140.0	177	97.4	99.1	101.6	78.8	79.9	83.8	84.4	85.8	89.1	73.8	75.9	79.2
61	18:29	X2000	EB	140.0	169	96.2	97.3	104.3	78.2	79.0	83.4	82.9	83.8	87.9	71.9	72.7	77.7
63	18:48	X2000	WB	140.0	171	93.7	95.0	99.1	78.5	79.9	84.5	84.7	85.2	90.3	72.4	73.9	78.7
			_						_	70.5					-		
AVG		X2000	EB	140.0	173	96.4	97.6	101.7	77.3	78.5	82.3	82.9	84.3	87.8	71.9	73.1	77.6
			WB	140.0	168	93.2	94.8	99.2	77.3	78.6	83.1	84 9	85.9	90.5	71.4	72.4	78.6

. -

HIGH-SPEED TRAIN NOISE DATA: SWEDEN - SITE 3A (PRIMARY SITE) - MAY 23, 1995

EVE	TIME	TRAIND	DESCR	IPTION		MEASURED A-WEIGHTED SOUND LEVEL (dBA)												
NO.	OF DA	Туре	Dir.	Length	Speed	Ch1(25mEB/29.5mWB/1.5mH			Ch2(25mE	B/29.5mWE	3/5.0mH	Ch3(50mEB/54.5mWB/1.5mH			Ch4(75mEB/79.5mWB/1.5mH			
				(m)	(kph)	Lmax(s)	Lmax(f)	SEL	Lmax(s)	Lmax(f)	SEL	Lmax(s)	Lmax(f)	SEL	Lmax(s)	Lmex(f)	SEL	
72	9:22	X2000	WB	140.0	183	91.3	92.0	96.7	93.3	94.6	98.5	88.4	89.8	93.9	84.9	85.7	90.7	
74	9:48	X2000	WB	140.0	185	91.3	92.5	96.5	93.3	94.5	98.7	88.6	90.0	94.1	83.2	84.3	88.9	
78	10:43	X2000	WB	140.0	185	92.8	93.6	97.7	95.0	96.0	100.1	89.4	90.6	94.6	80.2	81.0	85.8	
79	11:32	X2000	EB	140.0	159	89.1	89.5	94.3	91.5	92.0	97.0	86.5	87.8	92.0	80.5	81.2	86.7	
80	13:31	X2000	EB	140.0	182	94.4	95.0	99.1	94.5	95.0	99.2	90.9	92.0	96.1	82.7	83.4	88.2	
82	14:04	X2000	WB	140.0	185	92.0	93.1	97.2	94.2	95.5	99.3	88.5	89.9	94.2	83.9	84.5	90.1	
83	16:32	X2000	EB	140.0	185	94.9	96.0	99.4	95.2	96.5	99.8	91.8	93.3	96.7				
85	16:55	X2000	WB	140.0	185	92.0	92.7	97.0	94.0	95.0	99.1	89.7	90.7	95.2	87.0	87.6	92.8	
86	17:30	X2000	EB	140.0	182	93.0	93.9	97.6	93.0	94.0	97.8	90.0	90.8	95.1	85.8	86.8	91.3	
87	18:31	X2000	EB	140.0	180	93.0	93.3	98.0	93.2	93.9	98.2	90.3	91.1	95.6	87.8	88.5	93.4	
AVG		X2000	EB	w∕o#79	182	93.8	94.6	98.5	94.0	94.9	98.8	90.8	91.8	95.9	85.4	86.2	91.0	
			WB		185	91.9	92.8	97.0	94.0	95.1	99.1	88.9	90.2	94.4	83.8	84.6	89.7	

.

HIGH-SPEED TRAIN NOISE DATA: SWEDEN - SITE 4 (CURVE SITE) - MAY 24, 1995

EVE	TIME	TRAIN D	ESCR	IPTION		MEASURED A-WEIGHTED SOUND LEVEL (dBA)												
NO.	OF DA	Туре	Dir.	Length	Speed	Ch1(25mE	B/29.5mW	3/1.5mH	Ch2(25mEB/29.5mWB/5.0mH C			Ch3(50mE	B/54.5mWB	/1.5mH	Ch4(75mEB/79.5mWB/1.5m			
				(m)	(kph)	Lmax(s)	Lmax(f)	SEL	Lmax(s)	Lmax(f)	SEL	Lmax(s)	Lmax(f)	SEL	Lmax(s)	Lmax(f)	SEL	
100	9:19	X2000	WB	140.0	175	80.8	83.9	87.1	86.1	88.0	91.0	77.8	78.9	84.1	77.0	77.5	83.3	
101	9:42	X2000	WB	140.0	174	83.2	84.3	89.0	87.8	89.1	92.4	79.8	80.9	84.9	77.8	78.6	87.4	
109	11:33	X2000	EB	140.0	174	86.9	88.5	91.3	87.4	89.2	91.7	82.5	83.6	87.4	78.9	79.9	84.6	
110	13:35	X2000	EB	140.0	72	77.0	78.0	84.4	77.6	78.4	85.1	71.7	72.1	80.2	68.0	68.0	76.9	
111	13:51	X2000	WB	140.0	183	84.9	86.0	90.0	89.2	90.0	94.3	80.3	81.0	86.1	80.0	80.2	86.2	
AVG		X2000	WB	140.0	177	83.0	84.7	88.7	87.7	89.0	92.6	79.3	80.3	85.0	78.3	78.8	85.6	

.-

HIGH-SPEED TRAIN NOISE DATA: SWEDEN - SITE 5 - MAY 24, 1995

EVE	TIME	TRAIN D	ESCR	IPTION		MEASURED A-WEIGHTED SOUND LEVEL (dBA)												
NO.	OF DA	Туре	Dir.	Length	Speed	Ch1(25mE	B/29.5mWE	3/1.5mH	Ch2(25mE	B/29.5mWE	¥5.0mH	Ch3(50mE	B/54.5mWE	V1.5mH	Ch4(75mEB/79.5mWB/1.5mH			
				(m)	(kph)	Lmax(s)	Lmax(f)	SEL	Lmax(s)	Lmax(f)	SEL	Lmax(s)	Lmax(f)	SEL	Lmax(s)	Lmax(f)	SEL	
121	16:38	X2000	EB	140.0	183	93.6	94.1	88.5	93.8	94.7	98.8	91.6	92.1	96.5	89.8	90.2	95.0	
122	16:44	X2000	WB	140.0	177	85.7	87.7	95.0	89.7	91.2	95.2	83.9	85.5	89.6	82.7	83.1	88.4	
124	17:38	X2000	EB	140.0	187	93.4	94.4	97.8	93.8	95.2	98.9	91.6	92.9	96.3	89.8	90.3	95.2	
125	18:37	X2000	EB	140.0	187	93.1	94.5	97.6	93.5	94.3	98.0	89.6	90.0	94.8	88.3	89.0	94.0	
126	18:42	X2000	WB	140.0	174	86.5	88.1	91.7	89.5	91.2	95.2	83.2	84.1	88.9	82.0	82.6	87.7	
128	19:38	X2000	WB	140.0	114	82.2	83.4	88.0	85.4	86.8	91.9	79.1	79.7	85.9	78.7	80.1	85.7	
AVC		¥2000	F D	140.0	190	02.4	04.2	04.6	027	047	00.0	00.0	017	05.0	00.0	00.0		
AVG		12000	CB	140.0	180	93.4	94.3	94.0	93.7	94.7	98.6	90.9	91.7	32.3	89.3	89.8	94.7	

-

APPENDIX B: TRAIN NOISE SPECTRA





FRANCE - SITE D (Primary) Far track TGV - Average spectra



FRANCE - SITE G (Cut) Near track TGV - Average spectra

2:293630WOISEDAT\SPECTRA\FAVGSPEC.WB1

09/07/95



FRANCE - SITE G (Cut) Far track TGV - Average spectra



FRANCE - SITE H1 (Barrier) Near track TGV - Average spectra

:\293630\NOISEDAT\SPECTRA\FAVGSPEC.WB1

09/07/95



FRANCE - SITE H1 (Barrier) Far track TGV - Average spectra



FRANCE - SITE H2 (No Barrier) Near track TGV - Average spectra


FRANCE - SITE H2 (No Barrier)





FRANCE - SITE K (Low Speed) Far track TGV - Average spectra



ITALY - SITE 4 (Primary) Near track Pendolino - Average spectra



ITALY - SITE 4 (Primary) Far track Pendolino - Average spectra















S:\PROJECTS\293630\VOISEDAT\SPECTRA\SAVGSPEC.WB1

09/08/95









SWEDEN - SITE 2 (Cut) Far track X2000 - Average spectra









PROJECTS\293630\NOISEDAT\SPECTRA\SAVGSPEC.WB1





::\PROJECTS\293630\NOISEDAT\SPECTRA\SAVGSPEC.WB1

09/08/95



.

APPENDIX C: GROUND-BORNE VIBRATION LEVELS FOR TRAIN EVENTS

HIGH-SPEED TRAIN VIBRATION DATA: FRANCE - SITE D (PRIMARY SITE) - MAY 10, 1995

EVEN	TIME	TRAIN DE	ESCRIP	TION	TON MEASURED MAXIMUM VERTICAL VIBRATION VELOCITY LEVEL (EVEL (VdB)					
NO.	OF DA	Туре	Dir.	Length	Speed	Ch1(17.5mSB/	22mNB)	Ch2(25mSB/	29.5mNB)	Ch3(37.5mS	B/42mNB)	Ch4(50mSB/	54.5mNB)	Ch5(62.5mSBA	67mNB)	Ch6(75mS8/7	9.5mNB)
				(m)	(kph)	RMSV	PPV	RMSV	PPV	PMSV	PPV	RMSV	PPV	RMSV	PPV	RMSV	PPV
2	12:18	TGV	NB	237.5	290	74.5	84.3	72.1	83.7	64.0	74.8	57.1	67.4	52.2	65.0	51.2	63.8
3	12:32	Eurostar	NB	393.7	290	74.8	84.2	71.0	83.2	64.2	75.5	59.0	70.0	54.0	66.2	53.2	63.1
4	12:54	TGV-2	NB	475.0	294	76.0	85.6	72.3	83.0	64.2	75.5	59.5	71.3	53.8	67.4	53.4	66.2
5	12:58	TGV	SB	237.5	290	78.1	89.8	75.0	89.2	68.8	80.3	60.8	71.7	55.3	67.9	54.8	65.8
6	13:10	TGV	SB	237.5	293	79.1	91.2	76.0	89.6	68.6	80.9	61.5	72.6	56.0	68.8	54.8	67.1
7	13:15	TGV	SB	237.5	296	78.8	90.1	75.1	91.0	68.0	78.4	61.0	72.7	55.3	70.5	54.1	67.0
8	13:17	TGV	NB	237.5	293	77.0	88.1	73.0	86.1	65.0	75.8	59.0	71.2	53.5	66.8	52.5	66.8
21	16:25	TGV	SB	237.5	296	80.0	93.7	77.1	90.5	70.0	81.0	61.2	73.1	55.8	68.0	54.5	66.1
22	16:33	Eurostar	SB	393.7	269	76.5	88.3	72.8	89.8	63.5	77.8	59.0	70.0	54.5	67.0	56.0	66.3
23	16:40	TGV	NB	237.5	294	74.8	84.5	71.5	84.0	63.5	75.2	58.0	70.4	52.3	71.4	52.0	64.8
24	16:44	TGV	SB	237.5	290			76.2	88.9	69.2	BO.1	60.8	71.1	55.8	66.4	55.0	64.8
25	16:51	TGV-2	SB	475.0	293	80.5	89.5	77.5	90.2	71.0	81.6	62.5	72.3	56.8	69.5	56.2	67.3
27-1	17:30	Eurostar	NB	393.7	293	74.5	90.4	71.5	82.3	64.6	75.3	58.0	68.0	53.0	65.2	52.0	64.9
27-2	17:31	Eurostar	SB	393.7	296	79.3	91.5	75.5	93.1	68.2	81.1	60.3	73.3	56.0	68.2	54.2	65.4
28	17:35	TGV	NB	237.5	286	75.0	87.9	727	85.1	63.8	77.0	57.2	69.7	53.0	66.8	51.0	63.6
29	17:39	TGV	NB	237.5	266	73.8	85.6	70.5	81.7	67.5	74.4	55.8	67.1	50.2	62.8	49.8	62.6
30	17:43	TGV	SB	237.5	294	79.5	90.6	77.8	89.4	69.2	80.5	61.3	71.5	55.7	69.7	54.1	65.8
31	17:52	TGV	NB	237.5	296	75.1	86.0	72.0	83.0	64.3	76.4	58.5	69.4	52.8	65.4	52.0	63.6
32	18:06	TGV	NB	237.5	283	75.0	86.2	72.5	89.4	63.0	76.8	57.0	74.1	51.8	68.8	50.2	68.5
33	18:07	TGV	SB	237.5	293	78.5	91.2	75.2	89.5	68.8	79.5	61.0	71.7	55.2	68.1	54.6	65.9
34	18:10	TGV	NB	237.5	294	75.6	88.9	T22	87.5	64.8	77.1	59.0	71.8	53.8	67.9	51.B	65.0
35	18:13	TGV	SB	237.5	296	80.0	92.4	76.5	89.1	69.0	80.4	60.3	73.3	55.6	68.5	54.1	64.6
38	18:30	TGV	S8	237.5	293	78.3	90.2	74.8	89.7	68.0	78.6	60.8	71.1	55.4	68.2	54.0	65.8
39	18:42	TGV	NB	237.5	296	74.6	84.3	71.5	83.4	63.8	74.3	58.5	69.4	52.0	65.4	52.1	65.2
40	18:44	TGV	SB	237.5	296	79.0	91.1	75.1	96.1	67.9	79.3	60.8	721	55.9	69.0	54.2	65.6
AVG		TGV	SB	237.5	294	79.0	91.1	75.9	90.3	68.8	79.9	61.0	72.1	55.6	68.5	54.4	65.9
			NB	237.5	289	75.0	86.2	72.0	84.9	64.4	75.8	57.8	70.1	52.4	66.7	51.4	64.9
AVG		Eurostar	SB	393.7	283	77.9	89.9	74.2	91.5	65.9	79.5	5 59.7	71.7	55.3	67.6	55.1	65.9
			NB	393.7	292	74.7	87.3	71.3	82.8	64.4	75.4	58.5	69.0	53.5	65.7	52.6	64.0

HIGH-SPEED TRAIN VIBRATION DATA: FRANCE - SITE K (LOW-SPEED SITE) - MAY 11, 1995

EVE	TIME	TRAIN	DESCF	RIPTION		MAX. VIBRA	TION VE	ELOCITY LE	VEL (VdB)
NO.	OF D	Туре	Dir.	Lengt	Speed	Ch1(25mNB/	29.5mS	Ch2(50mNE	8/54.5mSB)
				(m)	(kph)	RMSV	PPV	RMSV	PPV
41	16:30	TGV	SB	237.5	193	67.0	76.2	63.6	72.1
42	16:35	TGV	NB	237.5	198	67.1	76.9	64.1	73.7
43	16:40	Eurostar	SB	393.7	206	65.3	73.9	65.3	73.8
4 4	16:49	TGV	SB	237.5	201	65.8	74.3	64.0	71.8
45	16:52	TGV-2	SB	475.0	185	66.3	74.8	63.2	71.3
46	17:25	Eurostar	NB	393.7	145	65.6	74.2	58.6	67.2
48	17:33	Eurostar	SB	393.7	169	64.1	73.3	62.2	69.5
49	17:36	TGV	NB	237.5	193	69.9	78.7	63.9	72.9
50	17:45	TGV	NB	237.5	198	67.7	75.4	63.7	72.1
51	17:50	TGV	SB	237.5	201	66.4	75.3	64.4	72.0
52	18:02	TGV	NB	237.5	196	66.5	74.6	64.0	73.0
53	18:12	TGV	SB	237.5	182	65.3	74.1	62.7	70.8
55	18:35	TGV	NB	237.5	216	66.2	75.1	61.0	73.5
56	18:49	TGV	SB	237.5	196	66.0	75.1	63.3	72.3
57	19:00	TGV	NB	237.5	166	66.0	75.1	58.5	67.9
AVG		TGV	NB	237.5	195	67.2	76.0	62.5	72.2
			SB	237.5	195	66.1	75.0	63.6	71.8
AVG		Eurostar	NB	393.7	145	65.6	74.2	58.6	67.2
			SB	393.7	188	64.7	73.6	63.8	71.7

HIGH-SPEED TRAIN VIBRATION DATA: ITALY - SITE 2 (AT-GRADE SITE) - MAY 15, 1995

.

EVE	TIME	TRAIN D	ESCF	RIPTION		MEASURED MAXIMUM VERTICAL VIBRATION VELOCITY LEVEL (VdB)										
NO.	OF D	Туре	Dir.	Lengt	Speed	Ch1(12.5m	VB/16.2mS	Ch2(25mh	VB/28.7mS	Ch3(50mN	IB/53.7mS	Ch4(75mN	B/78.7mS			
				(m)	(kph)	RMSV	PPV	RMSV	PPV	RMSV	PPV	RMSV	PPV			
67	20:19	Pendolino	NB	236.6	194	84.2	94.2	77.2	84.7	69.3	77.7	65.3	75.0			
68-2	20:34	Pendolino	SB	236.6		76.6	86.5	69.0	76.5	64.0	70.3	60.8	68.3			
71	20:49	Pendolino	SB	236.6	190	77.1	87.0	68.9	77.7	64.0	72.2	60.0	67.5			

HIGH-SPEED TRAIN VIBRATION DATA: ITALY - SITE 3 (CURVE SITE) - MAY 17, 1995

EVE	TIME	TRAIN D	ESCR	IPTION		MEASURED MAXIMUM VERTICAL VIBRATION VELOCITY LEVEL (VdB)									
NO.	OF D	Туре	Dir.	Lengt	Speed	Ch1(17.5ml	NB/21.2mS	Ch2(25mN	IB/28.7mS	Ch3(50mN	B/53.7mS	Ch4(75mN	B/78.7mS		
				(m)	(kph)	RMSV	PPV	RMSV	PPV	RMSV	PPV	RMSV	PPV		
36	20:03	Pendolino	NB	236.6	132	73.6	84.5	70.0	77.3	68.1	75.2	58.6	66.1		
40	20:36	Pendolino	SB	236.6	148	73.1	79.3	73.6	77.0	66.2	71.1	60.4	66.3		
43	20:48	Pendolino	SB	236.6	130	73.3	82.4	72.1	77.8	69.0	73.8	61.1	66.9		
45	20:54	Pendolino	NB	236.6	154	76.5	84.7	72.8	80.3	69.1	75.2	60.0	65.6		

· .

HIGH-SPEED TRAIN VIBRATION DATA: ITALY - SITE 4 (PRIMARY SITE) - MAY 16 & 18, 1995

TIME	TRAIN DE	SCRIP	TION		MEASURED MAXIMUM VERTICAL VIBRATION VELOCITY LEVEL (VdB)											
OF DA	Туре	Dir.	Length	Speed	Ch2(10mSB/1	3.7mNB)	Ch3(25mSB/2	28.7mNB) C	74(37.5mSB/4	1.2mNB)	Ch5(50mS8/5	3.7mNB)	Ch6(62.5mSB/66	2mNB)	Ch7(75mSB	78.7mNB)
			(m)	(kph)	VRMS	PPV	VRMS	PPV	VRMS	PPV	VRMS	PPV	VRMS	PPV	VRMS	PPV
6, 1995																
7:56	Pendolino	SB	236.6		78.2	86.9	69.8	79.5	67.8	76.8	67.3	75.2	65.0	70.7	63.6	70.4
8:58	Pendolino	SB	236.6	175	78.7	88.2	73.0	82.4	67.0	76.1	65.0	74.2	63.4	71.8	63.1	70.5
9:59	Pendolino	NB	236.6	190	78.1	85.2	70.8	79.0	64.2	73.0	62.0	69.4	58.7	66.6	57.9	64.8
12:59	Pendolino	NB	236.6	193	77.9	86.5	70.9	78.8	65.5	72.9	62.7	69.8	60.0	67.1	592	65.2
14:02	Pendolino	S8	236.6	195	77.4	85.2	69.8	78.4	67.1	74.1	67.2	74.2	64.8	70.0	63.3	71.0
16:59	Pendolino	NB	236.6	193	78.0	86.4	69.8	78.4	65.9	73.7	63.8	70.9	60.2	66.9	59.4	66.1
8, 1995																
7:57	Pendolino	SB	236.6	182	77.6	86.2	71.2	79.6	68.8	76.1	66.3	74.2			62.2	69.2
8:59	Pendolino	SB	236.6	196	77.2	85.4	69.9	78.5	67.0	75.8	67.0	72.9			62.8	69.4
9:18	Pendolino	SB	236.6	185	77.2	85.6	71.6	79.2	69.0	75.9	66.1	73.2			62.5	69.4
10:00	Pendolino	NB	236.6	192	77.1	86.2	70.1	78.1	64.9	73.9	63.0	70.4	59.1	67.4	58.4	65.2
	Pendolino	S8	236.6	187	77.7	86.3	70.9	79.6	67.8	75.8	66.5	74.0	64.4	70.8	62.9	70.0
		NB	236.6	192	77.8	86.1	70.4	78.6	65.1	73.4	62.9	70.1	59.5	67.0	58.7	65.3
	TIME OF DA 6, 1995 7:56 8:58 9:59 12:59 14:02 16:59 8, 1995 7:57 8:59 9:18 10:00	TIME TRAIN DE OF DA Type 6, 1995 7:56 Pendolino 8:58 Pendolino 9:59 Pendolino 14:02 Pendolino 14:02 Pendolino 8, 1995 7:57 Pendolino 8:59 Pendolino 9:18 Pendolino 10:00 Pendolino	TIME TRAIN DESCRIP OF DA Type Dir. 6, 1995 7:56 Pendolino SB 8:58 Pendolino SB 9:59 Pendolino NB 12:59 Pendolino NB 8:19:59 Pendolino NB 14:02 Pendolino SB 8:59 Pendolino SB 16:59 Pendolino SB 8:59 Pendolino SB 9:18 Pendolino SB 10:00 Pendolino SB Pendolino SB NB NB NB	TIME TRAIN DESCRIPTION OF DA Type Dir. Length (m) 6, 1995 Endolino S8 236.6 7:56 Pendolino S8 236.6 9:59 Pendolino NB 236.6 12:59 Pendolino NB 236.6 14:02 Pendolino NB 236.6 8, 1995 S8 236.6 S8 7:57 Pendolino S8 236.6 8:59 Pendolino S8 236.6 9:18 Pendolino S8 236.6 10:00 Pendolino S8 236.6 10:00 Pendolino S8 236.6 Pendolino S8 236.6 NB 10:00 Pendolino NB 236.6 Pendolino NB 236.6 NB 10:00 Pendolino NB 236.6 NB 236.6 NB 236.6	TIME TRAIN DESCRIPTION OF DA Type Dir. Length Speed. (m) 6, 1995 (kph) (kph) 7:56 Pendolino S8 236.6 8:58 Pendolino S8 236.6 193 12:59 Pendolino S8 236.6 193 14:02 Pendolino S8 236.6 193 8, 1995 S8 236.6 193 7:57 Pendolino S8 236.6 182 9:18 Pendolino S8 236.6 182 9:18 Pendolino S8 236.6 193 10:00 Pendolino S8 236.6 182 10:00 Pendolino S8 236.6 193 9:18 Pendolino S8 236.6 192 Pendolino N8 236.6 185 10:00 Pendolino N8 236.6 187 NB 236	TIME TRAIN DESCRIPTION OF DA Type Dir. Length Speed Ch2(10mSB/1 (kph) 6, 1995	TIME TRAIN DESCRIPTION OF DA Type Dir. Length Speed Ch2(10mSB/13.7mNB) 6,1995 (kph) VRMS PPV 7:56 Pendolino SB 236.6 78.2 86.9 8:58 Pendolino SB 236.6 175 78.7 88.2 9:59 Pendolino NB 236.6 190 78.1 852 12:59 Pendolino NB 236.6 193 77.9 86.5 14:02 Pendolino NB 236.6 193 77.4 85.2 16:59 Pendolino NB 236.6 193 78.0 86.4 8, 1995 - - 77.4 85.2 85.9 Pendolino SB 236.6 193 77.2 85.4 9:18 Pendolino SB 236.6 195 77.1 86.2 10:00 Pendolino SB 236.6 192 77.1 86.3 </td <td>TIME TRAIN DESCRIPTION N OF DA Type Dir. Length Speed Ch2(10mSB/13.7mN8) Ch3(25mSB/27mS</td> <td>TIME TRAIN DESCRIPTION MEASURED OF DA Type Dir. Length. Speed Ch2(10mSB/13.7mN8) Ch3(25mSB/23.7mN8) Ch3(25</td> <td>TIME TRAIN DESCRIPTION MEASURED MAXIMUM VE OF DA Type Dir. Length Speed Ch2(10mSP/13.7mNB) Ch3(25mSB/26.7mNB) Ch4(37.5mSB/46.7mNB) Ch4(37.5mSB/46</td> <td>TIME TRAIN DESCRIPTION MEASURED MAXIMUM VERTICAL VI OF DA Type Dir. Length Speed Ch2(10mS8/13.7mNB) Ch3(25mS8/23.7mNB) CH4(37.5mS8/41.2mNB) 6,1995 VRMS PPV VRMS PPV VRMS PPV 6,1995 VRMS PPV VRMS PV VRMS PV 7:56 Pendolino SB 236.6 175 78.7 88.2 73.0 82.4 67.0 76.1 9:59 Pendolino NB 236.6 190 78.1 852 70.8 78.4 67.1 74.1 12:59 Pendolino NB 236.6 193 77.9 86.5 70.9 78.4 65.7 72.9 14:02 Pendolino NB 236.6 193 77.4 85.2 69.8 78.4 65.9 73.7 8,199 Pendolino SB 236.6 193 77.2 85.4 69.9 78.5 67.0 75.8</td> <td>TIME TRAIN DESCRIPTION MEASURED MAXIMUM VERTICAL VIBRATION VEL OF DA Type Dir. Length Speed Ch2(10mSB/13.7mNB) Ch3(25mSB/28.7mNB) Ch4(37.5mSB/41.2mNB) Ch5(30mSB/5 6, 1995 VRMS PV PR Addition Addition Addition Addition Addition Addition Addition Addition Add</td> <td>TIMAIN TRAIN DESCRIPTION MEASURED <</td> <td>TIME TRAIN DESCRIPTION MEASURED MAXIMUM VERTICAL VIBRATION VELOCITY LEVEL (VdB) OF DA Type Dir. Length Speed Ch2(10mSB/13.7mNB) Ch3(25mSB/23.7mNB) Ch4(37.5mSB/13.2mNB) Ch5(50mSB/53.7mNB) Ch6(62.5mSB/65.7mNB) 6,1995 Findolino SB 236.6 78.2 86.9 69.8 79.5 67.8 76.8 67.3 75.2 65.0 8:58 Pendolino SB 236.6 175 78.7 88.2 73.0 82.4 67.0 76.1 65.0 74.2 63.4 9:59 Pendolino NB 236.6 190 78.1 852 70.8 78.4 65.5 72.9 62.0 69.4 58.7 12:59 Pendolino NB 236.6 193 77.4 85.2 69.8 78.4 65.7 72.9 63.8 70.9 63.8 76.1 66.3 74.2 64.8 16:59 Pendolino NB 236.6 193 77.4 85.2</td> <td>TIME TRAIN DESCRIPTION MEASURED MAXIMUM VERTICAL VIBRATION VELOCITY LEVEL (VdB) OF DA Type Dir. Length Speed Ch2(10mSB/13.7mNB) Ch3(25mSB/28.7mNB) Ch4(37.5mSB/41.2mNB) Ch5(50mSB/53.7mNB) Ch6(62.5mSB/66.2mNB) 6,1995 - VRMS PPV VRMS PV VRMS PPV VRMS PPV VRMS PV VRMS PV VRMS PV VRMS PV VRMS PV VRMS PV VRMS</td> <td>TIME TRAIN DESCRIPTION MEASURED MAXIMUM VERTICAL VIBRATION VELOCITY LEVEL (VdB) Ch7(75mS8/ VRMS Ch7(75mS8/ VRMS PPV VRMS PPV Ch5(50mS8/53.7mNB) Ch6(62.5mS8/62.2mNB) Ch7(75mS8/ VRMS PPV VRMS PV VRMS PV<!--</td--></td>	TIME TRAIN DESCRIPTION N OF DA Type Dir. Length Speed Ch2(10mSB/13.7mN8) Ch3(25mSB/27mS	TIME TRAIN DESCRIPTION MEASURED OF DA Type Dir. Length. Speed Ch2(10mSB/13.7mN8) Ch3(25mSB/23.7mN8) Ch3(25	TIME TRAIN DESCRIPTION MEASURED MAXIMUM VE OF DA Type Dir. Length Speed Ch2(10mSP/13.7mNB) Ch3(25mSB/26.7mNB) Ch4(37.5mSB/46.7mNB) Ch4(37.5mSB/46	TIME TRAIN DESCRIPTION MEASURED MAXIMUM VERTICAL VI OF DA Type Dir. Length Speed Ch2(10mS8/13.7mNB) Ch3(25mS8/23.7mNB) CH4(37.5mS8/41.2mNB) 6,1995 VRMS PPV VRMS PPV VRMS PPV 6,1995 VRMS PPV VRMS PV VRMS PV 7:56 Pendolino SB 236.6 175 78.7 88.2 73.0 82.4 67.0 76.1 9:59 Pendolino NB 236.6 190 78.1 852 70.8 78.4 67.1 74.1 12:59 Pendolino NB 236.6 193 77.9 86.5 70.9 78.4 65.7 72.9 14:02 Pendolino NB 236.6 193 77.4 85.2 69.8 78.4 65.9 73.7 8,199 Pendolino SB 236.6 193 77.2 85.4 69.9 78.5 67.0 75.8	TIME TRAIN DESCRIPTION MEASURED MAXIMUM VERTICAL VIBRATION VEL OF DA Type Dir. Length Speed Ch2(10mSB/13.7mNB) Ch3(25mSB/28.7mNB) Ch4(37.5mSB/41.2mNB) Ch5(30mSB/5 6, 1995 VRMS PV PR Addition Addition Addition Addition Addition Addition Addition Addition Add	TIMAIN TRAIN DESCRIPTION MEASURED <	TIME TRAIN DESCRIPTION MEASURED MAXIMUM VERTICAL VIBRATION VELOCITY LEVEL (VdB) OF DA Type Dir. Length Speed Ch2(10mSB/13.7mNB) Ch3(25mSB/23.7mNB) Ch4(37.5mSB/13.2mNB) Ch5(50mSB/53.7mNB) Ch6(62.5mSB/65.7mNB) 6,1995 Findolino SB 236.6 78.2 86.9 69.8 79.5 67.8 76.8 67.3 75.2 65.0 8:58 Pendolino SB 236.6 175 78.7 88.2 73.0 82.4 67.0 76.1 65.0 74.2 63.4 9:59 Pendolino NB 236.6 190 78.1 852 70.8 78.4 65.5 72.9 62.0 69.4 58.7 12:59 Pendolino NB 236.6 193 77.4 85.2 69.8 78.4 65.7 72.9 63.8 70.9 63.8 76.1 66.3 74.2 64.8 16:59 Pendolino NB 236.6 193 77.4 85.2	TIME TRAIN DESCRIPTION MEASURED MAXIMUM VERTICAL VIBRATION VELOCITY LEVEL (VdB) OF DA Type Dir. Length Speed Ch2(10mSB/13.7mNB) Ch3(25mSB/28.7mNB) Ch4(37.5mSB/41.2mNB) Ch5(50mSB/53.7mNB) Ch6(62.5mSB/66.2mNB) 6,1995 - VRMS PPV VRMS PV VRMS PPV VRMS PPV VRMS PV VRMS PV VRMS PV VRMS PV VRMS PV VRMS PV VRMS	TIME TRAIN DESCRIPTION MEASURED MAXIMUM VERTICAL VIBRATION VELOCITY LEVEL (VdB) Ch7(75mS8/ VRMS Ch7(75mS8/ VRMS PPV VRMS PPV Ch5(50mS8/53.7mNB) Ch6(62.5mS8/62.2mNB) Ch7(75mS8/ VRMS PPV VRMS PV VRMS PV </td

HIGH-SPEED TRAIN VIBRATION DATA: SWEDEN - SITE 3B (PRIMARY SITE) - MAY 23, 1995

EVEN	TIME	TRAIN DE	SCRIP	TION			MEASURED MAXIMUM VERTICAL VIBRATION VELOCITY (VdB)											
NO.	OF DA	Туре	Dir.	Length	Speed	Ch2(7.5mWB/1	5.8mEB)	Ch3(15mWB	24.3mEB) C	14(25mWB/	34.3mEB) C	h5(37.5mWB/46	.8mEB)	Ch6(50mWBA	9.3mEB) C	h7(62_5mWB/7	1.8mEE)	
				(m)	(kph)	VRMS	PPV	VRMS	PPV	VRMS	PPV	VRMS	PPV	VRMS	PPV	VRMS	PPV	
62	9.23	X2000	WB	140 0	183	87.0	99.2	84.3	91.2	83.0	89.6	75.4	82.1	76.2	83.2	77.8	86.0	
64	9:47	X2000	WB	140.0	185	85.5	94.7	83.2	90.7	82.3	89.1	73.3	79.8	75.5	81.5	76.7	84.4	
67	10:43	X2000	WB	140.0	185	86.1	95.9	83.2	91.6	82.1	89.1	70.0	772	76.0	82.3	77.0	84.1	
69	11:32	X2000	EB	140.0	159	90.0	99.5	85.0	90.9	82.2	88.0	69.2	74.5	76.0	82.6	77.5	82.8	
70	13:31	X2000	EB	140.0	182	84.3	93.6	82.7	90.1	85.0	90.1	74.4	812	77.7	84.4	79.0	84.5	
73	14:04	X2000	WB	140 0	185	86.1	95.4	83.1	92.5	81.3	89.4	74.2	82.1	76.5	83.3	76.1	83.0	
15	16:32	X2000	EB	140.0	185	83.6	92.4	83.4	91.3	83.2	90.1	77.1	82.7	79.0	85.2	77.4	84.9	
18	16:54	X2000	WB	140.0	185	85.4	95.3	83.5	91.2	82.0	91.3	78.0	87.6	76.1	81.9	76.4	84.E	
20	17:30	X2000	EB	140.0	182	84.0	91.1	82.5	90.2	84.9	90.5	78.3	83.7	78.0	83.8	79.0	84.3	
25	18:31	X2000	EB	140.0	180	83.7	92.1	82.3	89.1	84.5	90.2	78.0	84.3	76.8	83.7	78.4	85.3	
26	18:49	X2000	WB	140.0	188	87.3	97.9	84.2	93.0	82.0	89.3	79.2	86.8	77.1	83.5	77.8	85.E	
AVG		X2000	WB		185	86.2	96.4	83.6	91.7	82.1	89.6	75.0	82.6	76.2	82.6	77.0	84.7	
			EB	w/o#69	182	83.9	92.3	82.7	90.2	84.4	90.2	77.0	83.0	77.9	84.3	78.5	84.8	

HIGH-SPEED TRAIN VIBRATION DATA: SWEDEN - SITE 4 (CURVE SITE) - MAY 24, 199

EVE	TIME	TRAIN [DESCF	RIPTION		MAXIMUM V	ERTICA	L VIB. VELC	DCITY (V
NO.	OF D	Туре	Dir.	Lengt	Speed	Ch1(7.5mEE	3/12mW	Ch2(15mEl	3/19.5m
				(m)	(kph)	VRMS	PPV	VRMS	PPV
30	9:19	X2000	WB	140.0	175	86.2	98.3	83.3	91.7
31	9:42	X2000	WB	140.0	174	85.9	98.6	83.1	90.5
40	11:33	X2000	EB	140.0	174	89.8	99.7	83.0	91.4
41	13:35	X2000	EB	140.0	72	82.1	91.5	76.6	84.1
42	13:51	X2000	WB	140.0	183	86.5	98.2	83.0	92.1
AVG		X2000	WB	140.0	177	86.2	98.4	83.1	91.4

HIGH-SPEED TRAIN VIBRATION DATA: SWEDEN - SITE 5 - MAY 24, 1995

EVE	TIME	TRAIN D	ESCR	IPTION		MEASURED A-WEIGHTED SOUND LEVEL (dBA)										
NO.	OF DA	Туре	Dir.	Length	Speed	Ch1(7.5mE	B/12mW	Ch2(15mE	3/19.5mW	Ch3(25mEl	3/29.5mW	Ch4(50mE	B/54.5mW			
				(m)	(kph)	VRMS	PPV	VRMS	PPV	VRMS	PPV	VRMS	PPV			
44	16:38	X2000	EB	140.0	183	87.7	100.4	75.5	84.0	79.0	89.7	70.9	79.1			
45	16:44	X2000	WB	140.0	177	82.3	94.0	71.2	79.8	74.8	85.9	67.2	77.3			
47	17:38	X2000	EB	140.0	187	88.0	100.8	75.2	84.0	79.1	92.4	70.1	79.1			
48	18:37	X2000	EB	140.0	187	88.2	101.0	75.4	83.5	79.3	92.5	70.0	78.2			
49	18:42	X2000	WB	140.0	174	81.7	92.9	70.5	80.4	75.2	87.6	67.0	75.6			
50	19:38	X2000	WB	140.0	114	76.3	88.2	70.5	79.7	73.0	84.2	59.2	69.0			
AVG		X2000	EB	140.0	186	88.0	100.7	75.4	83.8	79.1	91.5	70.3	78.8			

.

APPENDIX D: GROUND-BORNE VIBRATION SPECTRA FOR TRAIN EVENTS





FRA High Speed Rail Vibration Spectra



FRA High Speed Rail Vibration Spectra


































hmmh

HARRIS MILLER MILLER & HANSON INC.

15 New England Executive Park Burlington, MA 01803 USA Tel. (617) 229-0707 Fax. (617) 229-7939 945 University Avenue Sacramento, CA 95825 USA Tel. (916) 568-1116 Fax (916) 568-1201 The Green Business Centre The Causeway, Staines, Middx TW18 3AL UK Tel. (44) 1784 449974 Fax (44) 1784 460347