



RF Energy Exposure Guide for Meteorcomm PTC Radios Installed in Vehicles or at Fixed Sites

IMPORTANT

Before installing, maintaining or using your radio, read this guide, which contains important RF energy awareness and control information and operational instructions to ensure compliance with FCC or Industry Canada RF exposure guidelines.

IMPORTANT

Retain this guide at the location of the radio installation.

Document Number: 00002628-A

This page intentionally left blank.

This work was funded in whole or in part by the Federal Railroad Administration, US Department of Transportation under U.S. Government Grant FR-TEC-0003-11-01-00, and is therefore subject to the following license: The Government is granted for itself and others acting on its behalf a paid-up, nonexclusive, irrevocable worldwide license in this work to reproduce, prepare derivative works, distribute copies to the public, and perform publicly and display publicly, by or behalf of the Government. All other rights are reserved by the copyright owner.

By downloading, using, or referring to this document or any of the information contained herein you acknowledge and agree:

Ownership

This document and the information contained herein are the property of Meteorcomm LLC ("MCC"). Except for a limited review right, you obtain no rights in or to the document, its contents, or any related intellectual property.

Limited Use and Non Disclosure

This document is protected by copyright, trade secret, and other applicable laws.

Disclaimer of Warranty

This document and all information contained within this document or otherwise provided by MCC, and all intellectual property rights within, are provided on an "as is" basis. MCC makes no warranties of any kind and expressly disclaims all warranties, whether express, implied or statutory, including, but not limited to warranties of merchantability, fitness for a particular purpose, title, non-infringement, accuracy, completeness, interference with quiet enjoyment, system integration, or warranties arising from course of dealing, usage, or trade practice.

Assumption of Risk

You are responsible for conducting your own independent assessment of the information contained in this document (including without limitation schematic symbols, footprints and layer definitions) and for confirming its accuracy. You may not rely on the information contained herein and agree to validate all such information using your own technical experts. Accordingly, you agree to assume sole responsibility for your review, use of, or reliance on the information contained in this document. MCC assumes no responsibility for, and you unconditionally and irrevocably release and discharge MCC and its affiliates and their respective officers, directors, and employees ("MCC Parties") from any and all loss, claim, damage or other liability associated with or arising from your use of any of the information contained in this document.

Limitation of Liability & Disclaimer

This document is disseminated under the sponsorship of the Department of Transportation in the interest of information exchange. The United States Government assumes no liability for its contents or use thereof.

In no event shall MCC or the MCC parties be liable for any indirect, incidental, exemplary, special, punitive, or treble or consequential damages or losses, whether such liability is based on contract, warranty, tort (including negligence), product liability, or otherwise, regardless as to whether they have notice as to any such claims.

Any opinions, findings, conclusions, or recommendations expressed in this publication are those of the author(s) and do not necessarily reflect the view of the Federal Railroad Administration and/or U.S. DOT. Trade or manufacturers' names any appear herein solely because they are considered essential to the objective of this report.

Hazardous Uses

None of the information contained in this document may be used in connection with the design, manufacture or use of any equipment or software intended for use in any fail safe applications or any other application where a failure may result in loss of human life or personal injury, property damage, or have a financial impact or in connection with any nuclear facility or activity or shipment or handling of any hazardous, ultra hazardous or similar materials ("Hazardous Uses"). MCC disclaims all liability of every kind for any Hazardous Uses, and you release MCC and the MCC Parties from and shall indemnify MCC and the MCC Parties against any such liability, including, but not limited to, any such liability arising from MCC's negligence.

Copyright and Trademark

Meteorcomm® and ITCnet® are registered trademarks of Meteorcomm LLC, and may not be used without express written permission of Meteorcomm LLC.

Trade or manufactures name may appear herein solely because they are considered essential to the objective of this report. The United States Government does not endorse products or manufacturers.

Document Number: 00002628- A

Revision History

Revision	Date	Description
1.0	12/15/2011	First draft of FRA document.

RF energy exposure awareness and control information, and operational instructions for FCC/IC occupational use requirements

NOTICE: This radio is intended for use in occupational/controlled conditions, where users have full knowledge of their exposure and can exercise control over their exposure to meet FCC/IC limits. This radio device is NOT authorized for general population, consumer, or any other use.

This two-way radio uses electromagnetic energy in the radio frequency (RF) spectrum to provide communications between two or more users over a distance. It uses RF energy or radio waves to send and receive messages. RF energy is one form of electromagnetic energy. Other forms include, but are not limited to, sunlight and x-rays. RF energy, however, should not be confused with these other forms of electromagnetic energy, which when used improperly, can cause biological damage. Very high levels of x-rays, for example, can damage tissues and genetic material.

Experts in science, engineering, medicine, health, and industry work with organizations to develop standards for safe exposure to RF energy. These standards provide recommended levels of RF exposure for both workers and the general public. These recommended RF exposure levels include substantial margins of protection.

All two-way radios marketed in North America are designed, manufactured, and tested to ensure they meet government-established RF exposure levels. In addition, manufacturers also recommend specific operating instructions to users of two-way radios. These instructions are important because they inform users about RF energy exposure and provide simple procedures on how to control it. Please refer to the following Web sites for more information on what RF energy exposure is and how to control your exposure to assure compliance with established RF exposure limits.

<http://www.fcc.gov/oet/rfsafety/rf-faqs.html>

<http://www.osha.gov/SLTC/radiofrequencyradiation/index.html>

FCC/ Industry Canada regulations

The FCC/IC rules require manufacturers to comply with the FCC/IC RF energy exposure limits for mobile two-way radios before they can be marketed in the U.S. or Canada as applicable. When two-way radios are used as a consequence of employment, the FCC/IC requires users to be fully aware of and able to control their exposure to meet occupational requirements. Your MCC user manuals and this RF Energy Exposure Guide include information and operating instructions required to control your RF exposure and to satisfy compliance requirements.

Compliance with RF exposure standard

Your MCC two-way radio is designed and tested to comply with a number of national and international standards and guidelines (listed below) regarding human exposure to radio frequency electromagnetic energy. This radio complies with the IEEE and ICNIRP exposure limits for occupational/controlled RF exposure environment at duty factors as shown in Tables 1 and 2 and is authorized by the FCC/IC for occupational use. In terms of measuring RF energy for compliance with the FCC/IC exposure guidelines, your radio antenna radiates measurable RF energy only while it is transmitting, not when it is receiving or in standby mode.

Your MCC two-way radio complies with the following RF energy exposure standards and guidelines as of the date of manufacture:

- U. S. Federal Communications Commission, Code of Federal Regulations; 47CFR Part 2 Subpart J
- Evaluating Compliance With FCC Guidelines for Human Exposure to Radiofrequency Electromagnetic Fields, OET Bulletin No. 65 (August 1997) and OET Bulletin No. 65 Supplement C (June 2001)
- Industry Canada RSS-102 Issue 4
- American National Standards Institute (ANSI) / Institute of Electrical and Electronic Engineers (IEEE) C95. 1-1992
- Institute of Electrical and Electronic Engineers (IEEE) C95.1-1999 Edition

Mobile installations: RF exposure compliance, control guidelines and operating instructions

To control exposure to yourself and others and to ensure compliance with occupational/controlled environment exposure limits, always adhere to the following procedures.

1. Guidelines

- These user awareness instructions should accompany the device or vehicle that it is installed in when transferred to other users.
- Do not use this device if the operational requirements described herein are not met.

2. Operator instructions

- Be aware that a transmitter may operate automatically at any time when functioning as a data radio. People outside of the vehicle must maintain the recommended minimum lateral distance from the antennas at all times. It is the responsibility of the vehicle's operator to keep bystanders beyond the minimum lateral distance from the antennas in order to comply with the FCC RF exposure limits for an uncontrolled/general population environment.
- Verify that people outside the vehicle are at least the recommended minimum lateral distance away, as shown in Table 1, from a properly installed externally-mounted antenna.
- The transmitter power is adjustable to accommodate the various installations of this product. Once the authorized ERP, antenna gain and the losses from feed line, connectors and any inline RF filters are known, the transmitter power must be evaluated and if necessary, set to a value that will ensure that the authorized ERP and RF exposure requirements are met. Refer to the user manual for the particular radio model for additional information regarding power adjustment.

Table 1 lists the recommended lateral distances to be maintained between bystanders and approved, properly installed mobile transmitting antennas in an uncontrolled environment.

Table 1: Rated power and recommended lateral distance from transmitting antennas in mobile applications

Radio type	Antenna type	Antenna gain (dBi)	Nominal PEP (watts)	Maximum duty cycle	Recommended minimum lateral distance from transmitting antenna	
					cm	in.
Wayside	¼-wave dipole mounted to roof or trunk of automobile	2.15	30	10%	31.6	12.4
Wayside	½-wave dipole mounted to roof or trunk of automobile	4.55	28.77	10%	40.4	15.9
Locomotive	Locomotive antenna 0 dBd mounted to roof of locomotive	2.15	50	30%	70	27.6

IMPORTANT

The licensee is required to comply with limits on frequency use, antenna location, power and effective antenna height per 47CFR Subpart T §90.701 et. seq., or Industry Canada SRSP-512 §6.3 as applicable.

Note: You, as the vehicle operator, should be knowledgeable of the location of each of the antennas on the vehicle and of the minimum lateral distances applicable to each. If this information is not available to you, contact your installer to obtain this information. Until this information is available to you, *keep bystanders at a distance beyond the largest lateral distance specified in Table 1 from every two-way radio antenna on the vehicle.*

Mobile antenna installation guidelines

The following instructions apply only to vehicles with metal bodies or suitable ground plane:

- Mount each antenna connected to a transmitter in the center of the roof or trunk lid of the vehicle. When mounting an antenna to a trunk lid, be sure the minimum lateral separation distances (Table 1) are maintained with respect to back seat passengers and people that might be standing next to a stationary vehicle.
- Install all antennas in accordance with the manufacturer's instructions.
- Always disable the transmitter when installing or servicing an antenna or transmission line or when working near an installed antenna.
- Use only MCC-approved or MCC-supplied antennas. Unauthorized antennas, modifications or attachments could damage the radio and their use may violate FCC or IC regulations.

Fixed installations: RF exposure compliance, control guidelines and operating instructions

To control exposure to yourself and others and to ensure compliance with RF exposure limits, always adhere to the following procedures:

- Base station or fixed antennas should be installed on permanent outdoor structures, such as the roof of a building or an antenna tower.
- Install all antennas in accordance with the manufacturer's instructions.
- Always disable the transmitter when installing or servicing an antenna or transmission line or when working near an installed antenna.
- Use only MCC-approved or MCC-supplied antennas. Unauthorized antennas, modifications or attachments could damage the radio and their use may violate FCC regulations.
- RF Exposure compliance at such sites must be addressed on a site-by-site basis. It is the responsibility of the licensee to ensure compliance is met.
- The transmitter power is adjustable to accommodate the various installations of this product. Once the authorized ERP, antenna gain and the losses from feed line, connectors and any inline RF filters are known, the transmitter power must be evaluated and if necessary, set

to a value that will ensure that the authorized ERP and RF exposure requirements are met. Refer to the user manual for the particular radio model for additional information regarding power adjustment.

Table 2 lists the recommended lateral distances to be maintained between bystanders and approved, properly installed fixed transmitting antennas in an uncontrolled environment.

Table 2: Rated power and recommended lateral distance from transmitting antennas in fixed applications

Radio type	Antenna type	Antenna gain (dBi)	Nominal PEP (watts)	Maximum duty cycle	Recommended minimum lateral distance from transmitting antenna	
					cm	inches
Wayside	2.0dBd exposed dipole tower leg-mounted fixed antenna	4.1	30	10%	39.6	15.6
Wayside	5.5dBd exposed dipole tower leg-mounted fixed antenna	7.6	14.26	10%	40.4	15.9
Base	2.0dBd exposed dipole leg-mounted fixed antenna	4.1	75	50%	140	55.0
Base	5.5dBd exposed dipole tower leg-mounted fixed antenna	7.6	75	50%	209	82.3

IMPORTANT

The licensee is required to comply with limits on frequency use, antenna location, power and effective antenna height per 47CFR Subpart T §90.701 et. seq., or Industry Canada SRSP-512 §6.3 as applicable.

Approved accessories

For a list of MCC-approved accessories, refer to the user manual, or contact MCC.

Meteorcomm LLC contact information

For additional information on exposure requirements or other information, contact the MCC factory at (253) 872-2521. Also, you may visit the MCC web site at www.meteorcomm.com or contact the Meteorcomm Service Desk.

There are several ways to contact the Meteorcomm Service Desk:

- Customers can log into the Service Desk directly at <https://support.meteorcomm.com>
 - Once registered, customers will be able to see all tickets that have been opened by their company. Customers will need to use an email address with their company as the domain. Using personal email accounts from (ie, Gmail, Yahoo, or Hotmail) will not allow MCC to link that user to their company's tickets in the Service Desk.
 - Once registered, customers can file support requests by accessing the Service Desk at the link above. Support ticket activity is sent to the users' email account so that customers are apprised of status as the ticket is updated.
- Customers can send an email to support@meteorcomm.com
 - An email sent by the customer will automatically generate a ticket in the Service Desk system.
 - Customers can then interact with MCC Service Desk Engineers via email or by logging into the system (using the URL provided in the first bullet above) to continue working on the issue.